

Safety Data Sheet (SDS) OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Page 1/9

Reviewed on 05/18/2015


| Identification   |  |  |  |
|--|--|--|--|
| Product identifier   |  |  |  |
| Trade name: Ecoli  |  |  |  |
| Low VOC Cleaner/L  |  | lified to MIL-PRF-68   | 30C Type V   |
| Product description  | Part No.   | Packaging  | National Stock Number                                  |
| Ecolink 250-SS   | 250-55   |  | 6850-01-584-7227                                       |
| Ecolink 250-SS   |  |  |  |
| Ecolink 250-SS<br>Ecolink 250-SS   | 250-5<br>250-1   | 5 Gal Pail<br>4 x 1 Gal Case   | 6850-01-584-7241<br>6850-01-584-7237                   |
| Application of the   |  |  |  |
| Details of the supp  |  |  | C C  |
| Manufacturer / Sup   |  |  |  |
| Ecolink  |  |  |  |
| 2177 Flintstone Driv<br>Tucker, GA 30084   | e, Ste. A  |  |  |
| www.ecolink.com  |  |  | email: info@ecoli                                      |
| 800-886-8240 or 77   |  | -5 EST)  |  |
| Emergency teleph<br>Inside the U.S.: 800   |  | IENTRAC 24 UNI   | PS)  |
| Outside the U.S.: 3  |  |  |  |
|  |  |  |  |
|  |  | or mixture   |  |
| Classification of th   |  | or mixture   |  |
| Classification of th   | <b>ne substance</b><br>ealth hazard  | <b>or mixture</b><br>damaging fertility or   | the unborn child.                                      |
| Classification of the GHS08 He Repr. 2 H361  | ne substance of a sub | damaging fertility or  | the unborn child.                                      |
| Classification of the GHS08 He Repr. 2 H361<br>Flam. Liq. 4 H227   | <b>he substance</b><br>ealth hazard<br>Suspected of c<br>Combustible li  | damaging fertility or<br>quid.   | the unborn child.                                      |
| Repr. 2         H361           Flam. Liq. 4         H227           Eye Irrit. 28         H320  | <b>he substance</b><br>ealth hazard<br>Suspected of c<br>Combustible li  | damaging fertility or<br>quid.   | the unborn child.                                      |
| Classification of the GHS08 He Repr. 2 H361<br>Flam. Liq. 4 H227<br>Eye Irrit. 28 H320<br>Label elements   | ne substance of<br>ealth hazard<br>Suspected of of<br>Combustible lin<br>Causes eye irr  | damaging fertility or<br>quid.   | the unborn child.                                      |
| Classification of the<br>Classification of the<br>GHS08 He<br>Repr. 2 H361<br>Flam. Liq. 4 H227<br>Eye Irrit. 28 H320<br>Label elements<br>GHS label elements<br>The product is class  | ne substance of<br>ealth hazard<br>Suspected of of<br>Combustible life<br>Causes eye irr<br>sified and label   | damaging fertility or<br>quid.<br>ritation.  | the unborn child.<br>Globally Harmonized System (GHS). |
| Classification of the  | ne substance of<br>ealth hazard<br>Suspected of of<br>Combustible life<br>Causes eye irr<br>sified and label   | damaging fertility or<br>quid.<br>ritation.  |  |
| Classification of the<br>Classification of the<br>GHS08 He<br>Repr. 2 H361<br>Flam. Liq. 4 H227<br>Eye Irrit. 28 H320<br>Label elements<br>GHS label elements<br>The product is class  | ne substance of<br>ealth hazard<br>Suspected of of<br>Combustible life<br>Causes eye irr<br>sified and label   | damaging fertility or<br>quid.<br>ritation.  |  |
| Classification of the<br>Classification of the<br>GHS08 He<br>Repr. 2 H361<br>Flam. Liq. 4 H227<br>Eye Irrit. 28 H320<br>Label elements<br>GHS label elements<br>The product is class  | ne substance of<br>ealth hazard<br>Suspected of of<br>Combustible life<br>Causes eye irr<br>sified and label   | damaging fertility or<br>quid.<br>ritation.  |  |
| Classification of the<br>Classification of the<br>GHS08 He<br>Repr. 2 H361<br>Flam. Liq. 4 H227<br>Eye Irrit. 28 H320<br>Label elements<br>GHS label elements<br>The product is class<br>Hazard pictograms   | ne substance of<br>ealth hazard<br>Suspected of of<br>Combustible life<br>Causes eye irr<br>sified and label   | damaging fertility or<br>quid.<br>ritation.  |  |
| Classification of the<br>Classification of the<br>GHS08 He<br>Repr. 2 H361<br>Flam. Liq. 4 H227<br>Eye Irrit. 28 H320<br>Label elements<br>GHS label elements<br>The product is class  | ne substance of<br>ealth hazard<br>Suspected of of<br>Combustible life<br>Causes eye irr<br>sified and label   | damaging fertility or<br>quid.<br>ritation.  |  |
| Classification of the<br>GHS08 He<br>Repr. 2 H361<br>Flam. Liq. 4 H227<br>Eye Irrit. 28 H320<br>Label elements<br>GHS label elements<br>Hazard pictograms<br>Hazard pictograms   | ne substance of ealth hazard<br>Suspected of of<br>Combustible lin<br>Causes eye irr   | damaging fertility or<br>quid.<br>ritation.  |  |
| Classification of the<br>Classification of the<br>GHS08 He<br>Repr. 2 H361<br>Flam. Liq. 4 H227<br>Eye Irrit. 28 H320<br>Label elements<br>GHS label elements<br>The product is class<br>Hazard pictograms<br>GHS08<br>Signal word Warning   | ne substance of a Combustible line Causes eye irresting and label s  | damaging fertility or<br>quid.<br>ritation.<br>ed according to the                                     |  |
| Classification of the<br>Classification of the                          | ne substance of a combustible line causes eye irrestified and labeled and labeled and labeled a substance of a  | damaging fertility or<br>quid.<br>ritation.<br>ed according to the<br>s of labeling:                   |  |
| Classification of the<br>Classification of the<br>Constraints of the | ne substance of a combustible line Causes eye irrestified and label solutions and substance subs | damaging fertility or<br>quid.<br>ritation.<br>ed according to the<br>s of labeling:                   |  |
| Classification of the<br>Classification of the                          | ne substance of<br>ealth hazard<br>Suspected of of<br>Combustible lin<br>Causes eye irr<br>sified and label<br>sified and label<br>s<br>fig component<br>asiloxane<br>combustible in   | damaging fertility or<br>quid.<br>ritation.<br>ed according to the<br><b>s of labeling:</b><br>liquid. |  |



INK.

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Reviewed on 05/18/2015



CAS: 111109-77-4 Dipropylene glycol dimethyl ether 2-5% Skin Irrit. 2, H315; Eye Irrit. 2A, H319; STOT SE 3, H335; Flam. Liq. 4, H227

(Contd. on page 3)

us



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Reviewed on 05/18/2015

Trade name: Ecolink 250-SS

#### 4 First-aid measures

#### · Description of first aid measures

• *Inhalation:* Supply fresh air. If not breathing, provide artificial respiration. Consult doctor if symptoms persist. In case of unconsciousness, place patient securely on side position for transportation.

· Skin contact: Generally the product does not irritate the skin. Wash areas with soap and water, remove contaminated clothing and shoes. If skin irritation occurs, consult a doctor.

• Eye contact: Remove contact lenses at once. Rinse opened eye, including under eyelids under running water for at least 15 minutes. If irritation persists, seek medical attention.

• **Swallowing:** Rinse out mouth and then drink plenty of water. **Do not induce vomiting**. If vomiting does occur, repeat fluid administration. If symptoms develop and/or persist, seek medical attention.

• Information for doctor: Treat symptomatically

• **Most important symptoms/effects, both acute and delayed:** Breathing difficulties. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

• Indication of any immediate medical attention and special treatment needed No further relevant information available.

## 5 Fire-fighting measures

• **Suitable Extinguishing media:** For small (incipient) fires, use regular foam, water fog, carbon dioxide or dry chemical. For large fires apply water from afar away as possible using very large quantities (flooding) applied as a mist or spray; solid streams of water may be ineffective. Cool affected containers with flooding quantities of water.

• **Special hazards arising from the substance or mixture:** Combustible liquid. Vapors can travel to a source of ignition and flash back. Explosive mixtures may occur at temperatures at or above flashpoint. If incinerated product will release the following toxic fumes: Carbon Oxides and Silicon Oxides.

• Advice for firefighters: Wear self-contained breathing apparatus (SCBA) pressure-demand (NIOSH approved or equivalent), and full protective gear to prevent contact with skin and eyes.

## 6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation, keep people at a distance and stay upwind. Avoid contact with skin, eyes and clothing. Beware of vapors accumulating to form explosive concentrations, vapors can accumulate in low areas. Keep away from ignition sources

· Environmental precautions: Do not allow to enter sewers/ surface or ground water.

• **Methods and material for containment and cleaning up:** Absorb with liquid-binding material (i.e. sand, diatomite, acid binders, universal binders, sawdust). Keep in suitable closed containers for disposal. Remove all sources of ignition, use spark proof tools and explosive proof equipment. Dispose contaminated material as waste according to section 13.

#### Reference to other sections

See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

(Contd. on page 4)



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Reviewed on 05/18/2015

#### Trade name: Ecolink 250-SS

## 7 Handling and storage

• **Precautions for safe handling:** Avoid contact with skin, eyes and clothing. Keep away from sources of ignition. Ensure good ventilation/exhaustion at the workplace. Open and handle receptacle with care. Prevent formation of mists/vapors Take measures to prevent electrostatic charge. Keep receptacles tightly sealed.

• Information about protection against explosions and fires: Protect from heat. Keep protective respiratory device available.

• **Conditions for safe storage, including any incompatibilities:** Store away from strong acids, strong bases, strong oxidizing agents and strong reducing agents.

• **Requirements to be met by storerooms and receptacles:** Store in a well ventilated place. Store in a cool, dry place away from sparks and flame. Do not store in direct sunlight.

# 8 Exposure controls/personal protection

#### · Control parameters

All ventilation should be designed in accordance with OSHA standard (29 CFR 1910.94). Use mechanical (general) ventilation for storage areas. Use appropriate ventilation as required to keep Exposure Limits in Air below TLV & PEL limits.

• **Components with occupational exposure limits:** The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

• Engineering Measures: Ensure adequate ventilation especially in confined areas, ensure eye wash stations and safety showers are close to work stations.

· Personal protective equipment:

• General protective and hygienic measures: The usual precautionary measures for handling chemicals should be followed. Keep away from foodstuffs, beverages. Immediately remove all soiled and contaminated clothing and wash before reuse. Wash hands before breaks and at the end of work. Store protective clothing separately. Avoid contact with the eyes and skin.

• **Breathing equipment:** Not necessary if room is well-ventilated. Where risk assessment shows airpurifying respirators are appropriate use a full face respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

• **Protection of hands:** Handle with gloves. Gloves must be inspected prior to use. Use chemical resistant gloves.

#### · Eye protection:



Wear appropriate protective glasses with side shields or chemical safety goggles. All eye protection should meet OSHA eye and face protection in regulations 29 CFR 1910.133 or NIOSH (US) or EN 166 (EU)

· Body protection: Wear appropriate impervious clothing to prevent skin exposure



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Reviewed on 05/18/2015

#### Trade name: Ecolink 250-SS

| 9 Physical and chemical prope  | ortios   |  |
|--|--|--|
| 9 Filysical and chemical prope   |  |  |
| <ul> <li>Information on basic physical and<br/>General Information</li> <li>Appearance:</li> </ul> | chemical properties                                  |  |
| Form:  | Liquid   |  |
| Color:   | Colorless  |  |
| · Odor:<br>· Odor threshold:   | Mild<br>Not determined.                              |  |
| · pH-value:  | Not determined.                                      |  |
| · Change in condition  |  |  |
| Melting point/Melting range:<br>Boiling point/Boiling range:                                       | Not determined.<br>185 °C (365 °F)                   |  |
| · Flash point:   | 63 °C (145 °F)                                       |  |
| · Flammability (solid, gaseous):   | Not applicable.                                      |  |
| · Ignition temperature:  | 388 °C (730 °F)                                      |  |
| · Decomposition temperature:   | Not determined.                                      |  |
| · Auto igniting:   | Product is not self-igniting.                        |  |
| · Danger of explosion:   | Not determined.                                      |  |
| • Explosion limits:<br>Lower:  | 0.7 Vol %  |  |
| Upper:   | Not determined.                                      |  |
| · Vapor pressure @ 20 °C (68 °F):  | <0.5 mm Hg   |  |
| · Density @ 20 °C (68 °F):   | 0.950-0.960 g/cm3 (7.92-8.01 lbs/gal)                |  |
| · Relative density   | Not determined.                                      |  |
| <ul> <li>Vapor density @ 20 °C (68 °F)</li> <li>Evaporation rate @ 20 °C (68 °F)</li> </ul>        | >1 (air=1)<br>0.04 (nBuAc=1)                         |  |
| · Solubility in   Miscibility with   |  |  |
| Water:   | Negligible   |  |
| · Partition coefficient (n-octanol/wate  | er): Not determined.                                 |  |
| · Viscosity:   |  |  |
| Dynamic:<br>Kinematic:   | Not determined.<br>Not determined.                   |  |
|  |  |  |
| VOC content:<br>· Other information  | 22 g/l<br>No further relevant information available. |  |

## 10 Stability and reactivity

· Chemical stability Stable under recommended storage conditions.

· Possibility of hazardous reactions: No dangerous reactions known

- **Conditions to avoid:** Elevated temperatures; decomposes with heat. Sources of ignition such as sparks, hot spots, welding, flames. Exposure to moist air or water.
- Incompatible materials: Strong acids, strong bases, strong oxidizing agents and strong reducing agents.
- · Hazardous decomposition products: Carbon Oxides and Silicon Oxides.



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

#### Trade name: Ecolink 250-SS

## 11 Toxicological information

- · Information on toxicological effects The toxicity of this product is unknown.
- · Acute toxicity:
- · Primary irritant effect:
- · on the skin: No irritating effect.
- on the eye: Irritating effect. Causes serious eye irritation.
- Additional toxicological information: The product shows the following dangers according to internally approved calculation methods for preparations: Irritant
- · Carcinogenic categories
- · IARC (international Agency for Research on Cancer)
- Group 1 Carcinogenic to humans Group 2A - Probably carcinogenic to humans Group 28 - Possibly carcinogenic to humans Group 3 - Not classifiable as to its carcinogenicity to humans Group 4 - Probably not carcinogenic to humans None of the ingredients are listed.
- **NTP (National Toxicology Program)** None of the ingredients are listed.
- OSHA-Ca (Occupational Safety & Health Administration) None of the ingredients are listed.



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Reviewed on 05/18/2015

Trade name: Ecolink 250-SS

## 12 Ecological information

- Toxicity The hazards for the aquatic environment are unknown.
- Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bio-accumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes: Not known to be hazardous to water.
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

## 13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage or any water system. ECOLINK 250-SS liquid is to be disposed of according to local, state, federal and international regulations. This combustible material may be burned in a chemical incinerator equipped with an afterburner and scrubber. Offer surplus and non-recyclable solutions to a licensed disposal company. Under RCRA, this material is not considered as hazardous.

• **Un-cleaned packaging's recommendation:** Dispose of as unused product. Disposal must be made according to official regulations.

## 14 Transport information

| · UN-Number<br>· DOT, ADR, ADN, IMDG, IATA   | Not Regulated               |
|--|-----------------------------|
| <ul> <li>UN proper shipping name</li> <li>DOT, ADR, ADN, IMDG, IATA</li> </ul>                 | Not Regulated               |
| <ul> <li>Transport hazard class(es)</li> </ul>   |                             |
| · DOT, ADR, ADN, IMDG, IATA<br>· Class   | Not Dangerous Goods         |
| <ul> <li>Packing group</li> <li>DOT, ADR, IMDG, IATA</li> </ul>                                | Not applicable              |
| · Environmental hazards:   | Not applicable.             |
| · Special precautions for user   | Not applicable.             |
| <ul> <li>Transport in bulk according to Annex II o<br/>MARPOL73178 and the IBC Code</li> </ul> | <b>f</b><br>Not applicable. |

us



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Reviewed on 05/18/2015

Trade name: Ecolink 250-SS

NK.

## 15 Regulatory information

- $\cdot$  Safety, health and environmental regulations/legislation specific for the substance or mixture  $\cdot$  Sara
- Section 355 (extremely hazardous substances): None of the ingredients are listed.
- Section 313 (Specific toxic chemical listings): This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels
- **TSCA (Toxic Substances Control Act):** All ingredients are listed.
- California Proposition 65 Chemicals known to cause cancer: None of the ingredients are listed.
- Chemicals known to cause reproductive toxicity for females: None of the ingredients are listed.
- Chemicals known to cause reproductive toxicity for males: None of the ingredients are listed.
- Chemicals known to cause developmental toxicity: None of the ingredients are listed.
- · Carcinogenic categories
- EPA (Environmental Protection Agency) None of the ingredients are listed.
- TLV (Threshold Limit Value established by ACGIH) None of the ingredients are listed.
- NIOSH-Ca (National Institute for Occupational Safety and Health) None of the ingredients are listed.
- GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms



· Signal word Warning

- · Hazard-determining components of labeling:
- Octamethylcyclotetrasiloxane

(Contd. on page 9)



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Reviewed on 05/18/2015

#### Trade name: Ecolink 250-SS

 Hazard statements Combustible liquid. Causes eye irritation. Suspected of damaging fertility or the unborn child. · Precautionary statements Keep away from flames and hot surfaces. - No smoking. Wear protective gloves eye protection lace protection. Wash thoroughly after handling. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.m, IF exposed or concerned: Get medical advice1attention. In case of fire: Use for extinction: CO2, powder or water spray. Store locked up. Store in a well-ventilated place. Keep cool. Dispose of contents/container in accordance with local, regional, national, international regulations. · National regulations: Pennsylvania and New Jersey Right to Know Components.

· State Right to Know

CAS: 541-02-6 Decamethylcyclopentasiloxane >50%

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

## 16 Other information

Ecolink, Inc. believes the information contained herein is accurate. However, Ecolink makes no warranty, expressed or implied, regarding the accuracy of this data or the results to be obtained by the use thereof. Ecolink, Inc. assumes no responsibility for injury from the use of the product described herein.

#### · Date of preparation / last revision 05/18/2015

· Abbreviations and acronyms: ADR: The European Agreement concerning the International Carriage of Dangerous Goods by Road ADN: The European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association ACGIH: American Conference of Governmental Industrial Hygienists EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, ÉU) Flam. Liq. 3: Flammable liquids, Hazard Category 3 Flam. Liq. 4: Flammable liquids, Hazard Category 4 Skin Irrit. 2: Skin corrosion1irritation, Hazard Category 2 Eye Irrit. 2A: Serious eye damage1eye irritation, Hazard Category 2A Eye Irrit. 2B: Serious eye damage1eye irritation, Hazard Category 2B Repr. 2: Reproductive toxicity, Hazard Category 2 STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3 Aquatic Chronic 4: Hazardous to the aquatic environment - Chronic Hazard, Category 4

SDS created by MSDS Authoring Services www.msdsauthoring.com (877) 204-9106