

Safety Data Sheet (SDS) OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Reviewed on 05/07/2015

1 Identification • Product identifier • Trade name: Heavyweight • Product description Non-Butyl Industrial Detergent Product Name Part No. Product Name Part No. Heavyweight 0282-55 0282-55 5 Gal Drums Heavyweight 0282-5 Non-Butyl 0282-1 Heavyweight 0282-1 Veatils of the supplier of the safety data sheet • Manufacturer/Supplier: Ecolink 2177 Flintstone Drive, Ste. A Tucker, GA 30084 www.ecolink.com 800-886-8240 or 770-621-8240 (8-5 EST) • Emergency telephone number: Inside the U.S.: 800-535-5053 (INFOTRAC, 24 HOURS) Outside the U.S.: 352-323-3500 (INFOTRAC, 24 HOURS)	email: info@ecolink.co
 Trade name: Heavyweight Product description Non-Butyl Industrial Detergent Product Name Part No. Packaging Heavyweight 0282-55 55 Gal Drums Heavyweight 0282-5 5 Gal Pail U282-1 4 x 1 Gal Pail Details of the supplier of the safety data sheet Manufacturer/Supplier: Ecolink 2177 Flintstone Drive, Ste. A Tucker, GA 30084 www.ecolink.com 800-886-8240 or 770-621-8240 (8-5 EST) Emergency telephone number: Inside the U.S.: 800-535-5053 (INFOTRAC, 24 HOURS) Outside the U.S.: 352-323-3500 (INFOTRAC, 24 HOURS) 	email: info@ecolink.co
Product description Non-Butyl Industrial Detergent Product Name Part No. Packaging Heavyweight 0282-55 55 Gal Drums Heavyweight 0282-5 5 Gal Pail Heavyweight 0282-1 4 x 1 Gal Pail Details of the supplier of the safety data sheet Manufacturer/Supplier: Ecolink 2177 Flintstone Drive, Ste. A Tucker, GA 30084 www.ecolink.com 800-886-8240 or 770-621-8240 (8-5 EST) Emergency telephone number: Inside the U.S.: 352-323-3500 (INFOTRAC, 24 HOURS) Outside the U.S.: 352-323-3500 (INFOTRAC, 24 HOURS)	email: info@ecolink.co
Non-Butyl Industrial Detergent Product Name Part No. Packaging Heavyweight 0282-55 55 Gal Drums Heavyweight 0282-5 5 Gal Pail Heavyweight 0282-1 4 x 1 Gal Pail Details of the supplier of the safety data sheet Manufacturer/Supplier: Ecolink 2177 Flintstone Drive, Ste. A Tucker, GA 30084 www.ecolink.com 800-886-8240 or 770-621-8240 (8-5 EST) Emergency telephone number: Inside the U.S.: 800-535-5053 (INFOTRAC, 24 HOURS) Outside the U.S.: 352-323-3500 (INFOTRAC, 24 HOURS)	email: info@ecolink.co
Heavyweight0282-5555 Gal DrumsHeavyweight0282-55 Gal PailHeavyweight0282-14 x 1 Gal PailDetails of the supplier of the safety data sheetManufacturer/Supplier:Ecolink2177 Flintstone Drive, Ste. ATucker, GA 30084www.ecolink.com800-886-8240 or 770-621-8240 (8-5 EST)Emergency telephone number:Inside the U.S.:800-535-5053 (INFOTRAC, 24 HOURS)Outside the U.S.:352-323-3500 (INFOTRAC, 24 HOURS)	email: info@ecolink.co
 Details of the supplier of the safety data sheet Manufacturer/Supplier: Ecolink 2177 Flintstone Drive, Ste. A Tucker, GA 30084 www.ecolink.com 800-886-8240 or 770-621-8240 (8-5 EST) Emergency telephone number: Inside the U.S.: 800-535-5053 (INFOTRAC, 24 HOURS) Outside the U.S.: 352-323-3500 (INFOTRAC, 24 HOURS) 	email: info@ecolink.co
Manufacturer/Supplier: Ecolink 2177 Flintstone Drive, Ste. A Tucker, GA 30084 www.ecolink.com 800-886-8240 or 770-621-8240 (8-5 EST) Emergency telephone number: Inside the U.S.: 800-535-5053 (INFOTRAC, 24 HOURS) Outside the U.S.: 352-323-3500 (INFOTRAC, 24 HOURS)	email: info@ecolink.co
Hazard(s) identification	
P. Hazard(s) identification	
Ole spitianting of the substance on mintage	
· Classification of the substance or mixture	
GHS07	
\checkmark	
Skin Irrit. 2 H315 Causes skin irritation.	
Label elements GHS label elements	
The product is classified and labeled according to the Globally Hazard pictograms	armonized System (GHS).
\wedge	
GHS07	
GHS07 Signal word Warning	

(Contd. on page 2)


uS

ia. Ecolink.

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Reviewed on 05/07/2015



Dangerous Compo	onents:	
CAS: 7601-54-9	Trisodium Orthophosphate	5-10
• • • • • • • • • • • •	Skin Irrit. 2, H315; Eye Irrit. 2A, H319; STOT SE 3, H335	
CAS: 34590-94-8	(2-methoxymethylethoxy)propanol	5-10
RTECS: JM 157500	00 Flam. Liq. 4, H227	



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Reviewed on 05/07/2015

Trade name: Heavyweight

4 First-aid measures

- · Description of first aid measures
- · After inhalation:

Supply fresh air. If required, provide artificial respiration. Consult doctor if symptoms persist. In case of unconsciousness, place patient securely on side position for transportation.

After skin contact:

Immediately wash with water and soap and rinse thoroughly. If skin irritation occurs, consult a doctor.

 After eye contact: Rinse opened eye for at least 15 minutes under running water. If symptoms persist, consult a doctor.
 After swallowing: Pinae out mouth and than drink plants of water.

Rinse out mouth and then drink plenty of water. Do not induce vomiting. If vomiting does occur, repeat fluid administration If symptoms develop and1or persist, seek medical attention.

- · Information for doctor:
- *Most important symptoms and effects, both acute and delayed:* No further relevant information available.
- Indication of any immediate medical attention and special treatment needed
 No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents: Use fire fighting measures that suit the environment.
- · Special hazards arising from the substance or mixture

If incinerated product will release the following toxic fumes: Carbon Oxides, Nitrogen Oxides (NOx), Phosphorous Oxides, Potassium Oxides and Sodium Oxides.

- · Advice for firefighters Use water spray to cool unopened containers.
- · Protective equipment:

As in any fire, wear self-contained breathing apparatus pressure-demand (NIOSH approved or equivalent), and full protective gear to prevent contact with skin and eyes.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation Keep people at a distance and stay upwind. Avoid contact with skin, eyes and clothing. Keep away from ignition sources

· Environmental precautions: Dilute with plenty of water.

(Contd. on page 4)



ia. Ecolink.

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Reviewed on 05/07/2015

Trade name: Heavyweight

- Methods and material for containment and cleaning up: Absorb with liquid-binding material (i.e. sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to section 13. Use neutralizing agent. Ensure adequate ventilation. Dispose of the collected material according to regulations.
- Reference to other sections
 See Section 7 for information on safe handling.
 See Section 8 for information on personal protection equipment.
 See Section 13 for disposal information.

7 Handling and storage

· Handling:

- Precautions for safe handling Avoid contact with skin, eyes and clothing Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols and spray mists. Keep receptacles tightly sealed.
- · Information about protection against explosions and fires: No special measures required.
- Conditions for safe storage, including any incompatibilities
 Store away from strong acids, strong oxidizing agents and strong reducing agents.
 Storage:
 Requirements to be met by storerooms and receptacles:
 - Store in a well ventilated place.

Store in a cool, dry place away from sparks and flame.

- Do not store in direct sunlight.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: None.
- Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see section 7.
- · Control parameters

All ventilation should be designed in accordance with OSHA standard (29 CFR 1910.94). Use mechanical (general) ventilation for storage areas. Use appropriate ventilation as required to keep Exposure Limits in Air below TLV & PEL limits.

· Components with occupational exposure limits:

7601-54-9 Trisodium Orthophosphate

WEEL Short-term value: 5 mg/m3

34590-94-8 (2-methoxymethylethoxy)propanol

- PEL Long-term value: 600 mg/m3, 100 ppm (Skin)
- REL Short-term value: 900 mg/m3, 150 ppm Long-term value: 600 mg/m3, 100 ppm (Skin)
- TLV Short-term value: 909 mg/m3, 150 ppm Long-term value: 606 mg/m3, 100 ppm (Skin)

(Contd. on page 5)

us

ia. Ecolink.

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Reviewed on 05/07/2015

Trade name: Heavyweight

- · Additional information: The lists that were valid during the creation of this SDS were used as basis.
- · Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures: The usual precautionary measures for handling chemicals should be followed. Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing and wash before reuse. Wash hands before breaks and at the end of work. Avoid contact with the skin. Avoid contact with the eyes and skin.
- · Breathing equipment:
- Not necessary if room is well-ventilated.

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure, use respiratory protective device that is independent of circulating air.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product. Due to missing tests no recommendation to the glove material can be given for the product. Select glove material based on penetration times, rates of diffusion and degradation.

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material cannot be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break-through time has to be determined and observed by the manufacturer of the protective gloves.

· Eye protection:



Goggles or safety glasses with side shields recommended during refilling.

· Body protection:



Protective work clothing

(Contd. on page 6)



Safety Data Sheet (SDS) OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Page 6/11

Reviewed on 05/07/2015

Trade name: Heavyweight

 Information on basic physical and General Information 	chemical properties	
Appearance: Form: Color: Odor: Odor threshold:	Liquid Light purple Mild Not determined.	
∙ pH-value @ 20 °C (68 °F):	12.0	
Change in condition Melting point/Melting range: Boiling point/Boiling range:	Not determined. 105 °C (221 °F)	
Flash point:	None.	
Flammability (solid, gaseous):	Not applicable.	
Ignition temperature:		
Decomposition temperature:	Not determined.	
Auto igniting:	Product is not self-igniting.	
Danger of explosion:	Product does not present an explosion haza	ard.
Explosion limits: Lower: Upper:	Not determined. Not determined.	
· Density @ 20 °C (68 °F): · Relative density	1.045 g/cm³ (8.72 lbs/gal) Not determined.	
· Evaporation rate	1.0 (water=1).	
Solubility in / Miscibility with Water:	Soluble.	
Partition coefficient (n-octanol/wat	er): Not determined.	
Viscosity: Dynamic: Kinematic:	Not determined. Not determined.	
 Solvent content: VOC content: Other information 	69 g/l No further relevant information available.	



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Reviewed on 05/07/2015

Trade name: Heavyweight

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability Stable under normal conditions.
- **Thermal decomposition** | **conditions to be avoided**: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- Conditions to avoid Elevated temperatures; decomposes with heat. Sources of ignition such as sparks, hot spots, welding, flames.
- · Incompatible materials: Strong acids, strong oxidizing agents and strong reducing agents.
- · Hazardous decomposition products:

Carbon Oxides, Nitrogen Oxides (NOx), Phosphorous Oxides, Potassium Oxides and Sodium Oxides.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · LD/LC50 values that are relevant for classification:

34590-94-8 (2-methoxymethylethoxy)propanol

Oral	LD50	5,135 mg/kg (rat)
Dermal	LD50	>19,000 mg/kg (rabbit)
Inhalative	LC50	196 hours >10.000 mg/l (Pimephales)

7320-34-5 Tetrapotassium Pyrophosphate

Oral	LD50	>2,000 mg/kg (mouse)
Dermal	LD50	>4,640 mg/kg (rabbit)

- · Primary irritant effect:
- · on the skin: Irritant to skin and mucous membranes.
- · on the eye: No irritating effect.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

- · Carcinogenic categories
- · IARC (International Agency for Research on Cancer)

None of the ingredients are listed.

• **NTP (National Toxicology Program)** None of the ingredients are listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients are listed.

(Contd. on page 8)



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Reviewed on 05/07/2015

Trade name: Heavyweight

12 Ecological information

- · Toxicity
- · Aquatic toxicity:

34590-94-8 (2-methoxymethylethoxy)propanol

EC50 1,919 mg/l (daphnia)

- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:
- Generally not hazardous for water.

Rinse off of bigger amounts into drains or the aquatic environment may lead to increased pH-values. A high pH-value harms aquatic organisms. In the dilution of the use-level the pH-value is considerably reduced, so that after the use of the product the aqueous waste, emptied into drains, is only low water-dangerous.

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Unused material may be washed down sewer in event of a spill. Used material must be tested for contaminants, and then disposed of in compliance with state, federal and local regs. Please call us for disposal assistance or related support.

- · Uncleaned packagings:
- · Recommendation:
- Dispose of as unused product.

Disposal must be made according to official regulations.

· Recommended cleansing agent: Water, if necessary with cleansing agents.

(Contd. on page 9)

us



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Reviewed on 05/07/2015

Trade name: Heavyweight

UN-Number DOT, ADR, ADN, IMDG, IATA	Non-Regulated Material
UN proper shipping name DOT, ADR, ADN, IMDG, IATA	Non-Regulated Material
Transport hazard class(es)	
DOT, ADR, ADN, IMDG, IATA Class	Non-Regulated Material
Packing group DOT, ADR, IMDG, IATA	Non-Regulated Material
Environmental hazards:	Not applicable.
Special precautions for user	Not applicable.
<i>Transport in bulk according to Annex</i> <i>MARPOL73178 and the IBC Code</i>	t II of Not applicable.
UN "Model Regulation":	-

15 Regulatory information

- \cdot Safety, health and environmental regulations1legislation specific for the substance or mixture \cdot Sara
- Section 355 (extremely hazardous substances): 7601-54-9 Trisodium Orthophosphate
- Section 313 (Specific toxic chemical listings): 7601-54-9 Trisodium Orthophosphate
- TSCA (Toxic Substances Control Act): All ingredients are listed.
- · California Proposition 65
- Chemicals known to cause cancer: None of the ingredients are listed
- Chemicals known to cause reproductive toxicity for females: None of the ingredients are listed.
- Chemicals known to cause reproductive toxicity for males: None of the ingredients are listed.
- Chemicals known to cause developmental toxicity: None of the ingredients are listed.

(Contd. on page 10) us



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Reviewed on 05/07/2015

Trade name: Heavyweight

INK.

- · Carcinogenic categories
- EPA (Environmental Protection Agency) None of the ingredients are listed.
- TLV (Threshold Limit Value established by ACGIH) None of the ingredients are listed.
- NIOSH-Ca (National Institute for Occupational Safety and Health) None of the ingredients are listed.
- · GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS). • Hazard pictograms



- · Signal word Warning
- Hazard-determining components of labeling: Trisodium Orthophosphate
- · Hazard statements Causes skin irritation.
- · Precautionary statements
- Wear protective gloves.
- Wash thoroughly after handling.
- Obtain special instructions before use.
- Do not handle until all safety precautions have been read and understood.
- Specific treatment (see supplementary first aid instructions on this Safety Data Sheet).
- IF exposed or concerned: Get medical advice/attention.
- If skin irritation occurs: Get medical advice/attention.
- If on skin: Wash with plenty of water.

Take off contaminated clothing and wash it before reuse. Store locked up.

Dispose of contents1container in accordance with local/regional/national/international regulations.

· National regulations:

The product is subject to be classified according with the latest version of the regulations on hazardous substances.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

(Contd. on page 11) uS



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Reviewed on 05/07/2015

Trade name: Heavyweight

16 Other information

Ecolink, Inc. believes the information contained herein is accurate. However, Ecolink makes no warranty, expressed or implied, regarding the accuracy of this data or the results to be obtained by the use thereof. Ecolink, Inc. assumes no responsibility for injury from the use of the product described herein.

- · Date of preparation / last revision 05/07/2015
- Abbreviations and acronyms:

ADR: The European Agreement concerning the International Carriage of Dangerous Goods by Road ADN: The European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association ACGIH: American Conference of Governmental Industrial Hygienists EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2 Eye Irrit. 2A: Serious eye damage/eye irritation, Hazard Category 2A Carc. 2: Carcinogenicity, Hazard Category 2 STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3 SDS created by MSDS Authoring Services www.msdsauthoring.com (877) 204-9106

us