

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Reviewed on 05/07/2015

email: info@ecolink.com

1 Identification

· Product identifier

· Trade name: QED-T

· Product description

QED-T is a petroleum/terpene solvent degreaser for heavy duty degreasing applications.

 Product Name
 Part No.
 Packaging

 QED-T
 0150-55
 55 Gal Drum

 QED-T
 0150-5
 5 Gal Pail

 QED-T
 0150-1
 4 x 1 Gal Case

- · Application of the substance Environmentally Preferred Solvent
- · Details of the supplier of the safety data sheet
- · Manufacturer Supplier:

Ecolink

2177 Flintstone Drive, Ste. A

Tucker, GA 30084

www.ecolink.com

800-886-8240 or 770-621-8240 (8-5 EST)

· Emergency telephone number:

Inside the U.S.: 800-535-5053 (INFOTRAC, 24 HOURS) Outside the U.S.: 352-323-3500 (INFOTRAC, 24 HOURS)

2 Hazard(s) identification



GHS02 Flame

Flam. Liq. 3 H226 Flammable liquid and vapor.



GHS08 Health hazard

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

- · Label elements
- · GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 2)



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Reviewed on 05/07/2015

Trade name: QED-T

· Hazard pictograms







GHS02

GHS07 GHS

· Signal word Danger

· Hazard-determining components of labeling:

Isoparaffinic Hydrocarbon d-limonene

· Hazard statements

Flammable liquid and vapor.

Causes skin irritation.

May cause an allergic skin reaction.

May be fatal if swallowed and enters airways.

· Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Use explosion-proof electrical/ventilating/lighting/equipment.

Avoid breathing dust/fume/gas/mist/vapors/spray.

Wear protective gloves / eye protection / face protection.

Wear protective gloves.

Ground/bond container and receiving equipment.

Keep container tightly closed.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Wash thoroughly after handling.

Contaminated work clothing must not be allowed out of the workplace.

If swallowed: Immediately call a poison center/doctor.

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

Specific treatment (see supplementary first aid instructions on this Safety Data Sheet).

Wash contaminated clothing before reuse.

If skin irritation occurs: Get medical advice/attention.

If skin irritation or rash occurs: Get medical advice/attention.

Do NOT induce vomiting.

In case of fire: Use for extinction: CO2, powder or water spray.

Take off contaminated clothing and wash it before reuse.

Store locked up.

Store in a well-ventilated place. Keep cool.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Classification system: NFPA/HMIS Definitions: 0-Least, 1-Slight, 2-Moderate, 3-High, 4-Extreme

· NFPA ratings (scale 0 - 4)



Health = 1 Fire = 2 Reactivity = 0

(Contd. on page 3)



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Reviewed on 05/07/2015

Trade name: QED-T

· HMIS-ratings (scale 0 - 4)

HEALTH *1
FIRE 2
REACTIVITY 0

*1 Health = *1

Fire = 2 Reactivity = 0

· Hazard(s) not otherwise classified (HNOC): None known

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.
- Dangerous Components:

CAS: 64742-48-9 Isopara

Isoparaffinic Hydrocarbon 60-80%

Asp. Tox. 1, H304; Flam. Liq. 4, H227

CAS: 5989-27-5 d-limonene 30-50%

RTECS: GW 6360000 Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Skin Irrit. 2,

H315; Skin Sens. 1, H317; Flam. Lig. 4, H227

4 First-aid measures

- · Description of first aid measures
- · After inhalation:

Supply fresh air. If required, provide artificial respiration. Consult doctor if symptoms persist. In case of unconsciousness, place patient securely on side position for transportation.

· After skin contact:

Immediately wash with water and soap and rinse thoroughly.

If skin irritation occurs, consult a doctor.

· After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· After swallowing:

Rinse out mouth and then drink plenty of water.

Do not induce vomitina.

If vomiting does occur, repeat fluid administration

If vomiting occurs, the head should be kept low so that the vomit does not enter the lungs (aspiration).

Once the vomiting ceases, place the person in the recovery position with the legs slightly raised.

If symptoms develop and/or persist, seek medical attention.

- Information for doctor:
- · Most important symptoms and effects, both acute and delayed:

No further relevant information available.

· Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures

- Extinguishing media
- · Suitable extinguishing agents: Regular foam, water fog, carbon dioxide or dry chemical. Class B.

(Contd. on page 4)



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Reviewed on 05/07/2015

Trade name: QED-T

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture

Combustible liquid. Vapors can travel to a source of ignition and flash back.

Explosive mixtures may occur at temperatures at or above flashpoint.

If incinerated product will release the following toxic fumes: Carbon Oxides, and unburnt hydrocarbon particulate.

- · Advice for firefighters Use water spray to cool unopened containers.
- · Protective equipment:

As in any fire, wear self-contained breathing apparatus pressure-demand (NIOSH approved or equivalent), and full protective gear to prevent contact with skin and eyes.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation

Keep people at a distance and stay upwind.

Avoid contact with skin, eyes and clothing.

Keep away from ignition sources

Wear protective equipment. Keep unprotected persons away.

- · Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- Methods and material for containment and cleaning up:

Absorb with liquid-binding material (i.e. sand, diatomite, universal binders), do NOT use sawdust. Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

Dispose of the collected material according to regulations.

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- · Handling:
- · Precautions for safe handling

Avoid contact with skin, eyes and clothing

Keep away from sources of ignition.

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols and spray mists.

Keep receptacles tightly sealed.

· Information about protection against explosions and fires:

Do not spray on a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Protect from heat.

Protect against electrostatic charges.

Conditions for safe storage, including any incompatibilities

Store away from strong acids, strong bases, strong oxidizing agents and strong reducing agents.

(Contd. on page 5)



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Reviewed on 05/07/2015

Trade name: QED-T

- · Storage:
- · Requirements to be met by storerooms and receptacles:

Store in a well ventilated place.

Store in a cool, dry place away from sparks and flame.

Do not store in direct sunlight.

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep receptacle tightly sealed.

Protect from heat and direct sunlight.

· Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see section 7.
- · Control parameters

All ventilation should be designed in accordance with OSHA standard (29 CFR 1910.94). Use mechanical (general) ventilation for storage areas. Use appropriate ventilation as required to keep Exposure Limits in Air below TLV & PEL limits.

· Components with occupational exposure limits:

5989-27-5 d-limonene

TWA Short-term value: 10 mg/m3

- · Additional information: The lists that were valid during the creation of this SDS were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

The usual precautionary measures for handling chemicals should be followed.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing and wash before reuse.

Wash hands before breaks and at the end of work.

Avoid contact with the skin. Avoid contact with the eyes and skin.

· Breathing equipment:

Not necessary if room is well-ventilated.

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure, use respiratory protective device that is independent of circulating air.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Select glove material based on penetration times, rates of diffusion and degradation.

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material cannot be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 6)



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Reviewed on 05/07/2015

Trade name: QED-T

· Penetration time of glove material

The exact break-through time has to be determined and observed by the manufacturer of the protective gloves.

· Eye protection:



Tightly sealed goggles or safety glasses with side shields

· Body protection:



Protective work clothing

9 Physical and chemical properties

- · Information on basic physical and chemical properties
- · General Information

· Appearance:

Form: Liquid Color: Colorless

Odor:

Odor threshold:
pH-value:

Light citrus Terpene

Not determined.

Not determined.

· Change in condition

Melting point/Melting range:
Boiling point/Boiling range:Not determined.
160 °C (320 °F)Flash point:40 °C (104 °F)Flammability (solid, gaseous):Not applicable.Ignition temperature:240 °C (464 °F)Decomposition temperature:Not determined.

· **Auto igniting:** Product is not self-igniting.

• Danger of explosion: Product is not explosive. However, formation of explosive

air/vapor mixtures are possible.

· Explosion limits:

Lower: 0.7 Vol % 5.6 Vol %

• Vapor pressure @ 20 °C (68 °F): 2.0 mm Hg

• **Density @ 20 °C (68 °F):** 0.775 g/cm³ (6.47 lbs/gal)

Relative density
 Vapor density
 Not determined.
 ~5.0 (air=1)

(Contd. on page 7)



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Reviewed on 05/07/2015

Trade name: QED-T

· Evaporation rate @ 20 °C (68 °F) 0.2 (nBuAc=1)

· Solubility in / Miscibility with

Water: Negligible

· Partition coefficient (n-octanol/water): Not determined.

· Viscosity:

Dynamic: Not determined. **Kinematic:** Not determined.

· Other information No further relevant information available.

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability Stable under normal conditions.
- · Thermal decomposition I conditions to be avoided:

No decomposition if used according to specifications.

- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid

Elevated temperatures; decomposes with heat. Sources of ignition such as sparks, hot spots, welding, flames.

· Incompatible materials:

Strong acids, strong bases, strong oxidizing agents and strong reducing agents.

· Hazardous decomposition products: Carbon Oxides.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · LDILC50 values that are relevant for classification:

64742-48-9 Isoparaffinic Hydrocarbon

 Oral
 LD50
 >5,000 mg/kg (rat)

 Dermal
 LD50
 >3,000 mg/kg (rabbit)

5989-27-5 d-limonene

 Oral
 LD50
 4,400 mg/kg (rat)

 Dermal
 LD50
 >5,000 mg/kg (rabbit)

- · Primary irritant effect:
- on the skin:

Irritant to skin and mucous membranes. May cause an allergic skin reaction.

- on the eye: No irritating effect.
- · Sensitization: Sensitization possible through skin contact.

(Contd. on page 8)



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Reviewed on 05/07/2015

Trade name: QED-T

· Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

Irritant

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)

Group 1 - Carcinogenic to humans

Group 2A - Probably carcinogenic to humans

Group 2B - Possibly carcinogenic to humans

Group 3 - Not classifiable as to its carcinogenicity to humans

Group 4 - Probably not carcinogenic to humans

5989-27-5 d-limonene

3

· NTP (National Toxicology Program)

None of the ingredients are listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients are listed.

12 Ecological information

- · Toxicity
- · Aquatic toxicity:

5989-27-5 d-limonene

EC50 0.36 mg/l (daphnia) (OECD Test Guideline 202)

- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

QED-T liquid is to be disposed of according to local, state, and federal regulations. Please call us if you need additional disposal information.

(Contd. on page 9)



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Reviewed on 05/07/2015

Trade name: QED-T

- · Uncleaned packagings:
- · Recommendation:

Disposal must be made according to official regulations.

Dispose of as unused product.

14 Transport information

· UN-Number

· **DOT** Non-Regulated Material*

·**IMDG, IATA** UN1993

· UN proper shipping name

· **DOT** Non-Regulated Material[^]

· IMDG UN1993 PETROLEUM DISTILLATES, N.O.S.

(iso and cycloalkanes (C10-C11), Dipentene) MARINE

POLLUTANT

· IATA PETROLEUM DISTILLATES, N.O.S.

· Transport hazard class(es)

· DOT

· Class Non-Regulated Material*

· ADR



· Class 3 (F1) Flammable liquids

· Label

· IMDG





· Class 3 Flammable liquids

· Label

·IATA



· Class 3 Flammable liquids

· **Label** 3 (6.1)

^{*} This material is not regulated under 49 CFR in a container of 119 gallon capacity or less when transported solely by land.



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Reviewed on 05/07/2015

Trade name: QED-T

· Packing group

· **DOT** Non-Regulated Material

· ADR, IMDG, IATA

· Environmental hazards: Product contains environmentally hazardous

substances: d-limonene

· Special precautions tor user Warning: Flammable liquids

Danger code (Kemler): 30EMS Number: F-E, S-E

Transport in bulk according to Annex II of

MARPOL73/78 and the IBC Code Not applicable.

· Transport/Additional information:

· ADR

· Excepted quantities (EQ) Code: E1

Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml

· IMDG

· Limited quantities (LQ) 5L

· Excepted quantities (EQ) Code: E1

Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific tor the substance or mixture
- · Sara
- · Section 355 (extremely hazardous substances):

None of the ingredients are listed.

Section 313 (Specific toxic chemical listings):

None of the ingredients are listed.

· TSCA (Toxic Substances Control Act):

All ingredients are listed.

- · California Proposition 65
- · Chemicals known to cause cancer:

None of the ingredients are listed.

· Chemicals known to cause reproductive toxicity tor females:

None of the ingredients are listed.

· Chemicals known to cause reproductive toxicity tor males:

None of the ingredients are listed.

(Contd. on page 11)



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Reviewed on 05/07/2015

Trade name: QED-T

· Chemicals known to cause developmental toxicity:

None of the ingredients are listed.

- · Carcinogenic categories
- · EPA (Environmental Protection Agency)

None of the ingredients are listed.

· TLV (Threshold Limit Value established by ACGIH)

None of the ingredients are listed.

· NIOSH-Ca (National Institute tor Occupational Safety and Health)

None of the ingredients are listed.

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms







GHS02

GHS07 GHS08

- · Signal word Danger
- · Hazard-determining components ot labeling:

Isoparaffinic Hydrocarbon

d-limonene

· Hazard statements

Flammable liquid and vapor.

Causes skin irritation.

May cause an allergic skin reaction.

May be fatal if swallowed and enters airways.

Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Use explosion-proof electrical/ventilating/lighting/equipment.

Avoid breathing dust/fume/gas/mist/vapors/spray.

Wear protective gloves | eye protection | face protection.

Wear protective gloves.

Ground/bond container and receiving equipment.

Keep container tightly closed.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Wash thoroughly after handling.

Contaminated work clothing must not be allowed out of the workplace.

If swallowed: Immediately call a poison center/doctor.

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water.

Specific treatment (see supplementary first aid instructions on this Safety Data Sheet).

Wash contaminated clothing before reuse.

If skin irritation occurs: Get medical advice/attention.

If skin irritation or rash occurs: Get medical advice/attention.

Do NOT induce vomiting.

(Contd. on page 12)





OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Reviewed on 05/07/2015

Trade name: QED-T

In case of fire: Use for extinction: CO2, powder or water spray.

Take off contaminated clothing and wash it before reuse.

Store locked up.

Store in a well-ventilated place. Keep cool.

Dispose of contents/container in accordance with local/regional/national/international regulations.

National regulations:

The product is subject to be classified according with the latest version of the regulations on hazardous substances.

· State Right to Know

CAS: 64742-48-9 Isoparaffinic Hydrocarbon

60-90%

Asp. Tox. 1, H304; Flam. Liq. 4, H227

CAS: 5989-27-5 d-limonene

25-50%

RTECS: GW 6360000 Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Skin Irrit. 2,

H315; Skin Sens. 1, H317; Flam. Liq. 4, H227

All ingredients are listed.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

Ecolink, Inc. believes the information contained herein is accurate. However, Ecolink makes no warranty, expressed or implied, regarding the accuracy of this data or the results to be obtained by the use thereof. Ecolink, Inc. assumes no responsibility for injury from the use of the product described herein.

· Date of preparation / last revision 05/07/2015

· Abbreviations and acronyms:

ADR: The European Agreement concerning the International Carriage of Dangerous Goods by Road

ADN: The European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

Flam. Liq. 3: Flammable liquids, Hazard Category 3

Flam. Liq. 4: Flammable liquids, Hazard Category 4

Skin Irrit. 2: Skin corrosion1irritation, Hazard Category 2

Skin Sens. 1: Sensitization - Skin, Hazard Category 1

Asp. Tox. 1: Aspiration hazard, Hazard Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - AcuteHazard, Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - Chronic Hazard, Category 1

SDS created by MSDS Authoring Services www.msdsauthoring.com (877) 204-9106