

email: info@ecolink.com



# Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 09/23/2019 Reviewed on 09/23/2019

### 1 Identification

· Product Identifier

· Trade Name: Positron

 Part Number
 Packaging
 National Stock Number

 060-55
 55-Gal Drum
 6850-01-412-0028

 030-5
 5-Gal Pail
 6850-01-412-0026

 060-1
 4x1-Gal Case
 6850-01-411-8815

- · Relevant identified uses of the substance or mixture and uses advised against:
- · Product Description: Ultra-High Purity Dielectric Solvent
- · Details of the Supplier of the Safety Data Sheet:
- Manufacturer/Supplier:

**Ecolink** 

2177A Flintstone Drive

Tucker, GA 30084

www.ecolink.com

800-886-8240 or 770-621-8240 (8–5 EST)

· Emergency telephone number: PERS Emergency response: 1-801-629-0667

### 2 Hazard(s) Identification

· Classification of the substance or mixture:



Health hazard

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



Skin Irrit. 2 H315 Causes skin irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction. STOT SE 3 H336 May cause drowsiness or dizziness.

Flam. Liq. 4 H227 Combustible liquid.

- · Label elements:
- · Hazard pictograms:





- · Signal word: Danger
- · Hazard-determining components of labeling:

Distillates (petroleum), hydrotreated light

d-limonene

· Hazard statements:

H227 Combustible liquid.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H336 May cause drowsiness or dizziness.

H304 May be fatal if swallowed and enters airways.

(Contd. on page 2)



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 09/23/2019 Reviewed on 09/23/2019

Trade Name: Positron

 Part Number
 Packaging
 National Stock Number

 060-55
 55-Gal Drum
 6850-01-412-0028

 030-5
 5-Gal Pail
 6850-01-412-0026

 060-1
 4x1-Gal Case
 6850-01-411-8815

#### · Precautionary statements:

P210 Keep away from flames and hot surfaces. – No smoking. P261 Avoid breathing dust/fume/gas/mist/vapors/spray.

P264 Wash thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P272 Contaminated work clothing must not be allowed out of the workplace.
P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301+P310 If swallowed: Immediately call a poison center/doctor.

P321 Specific treatment (see supplementary first aid instructions on this Safety Data Sheet).

P331 Do NOT induce vomiting.

P302+P352 If on skin: Wash with plenty of water.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P312 Call a poison center/doctor if you feel unwell.

P362+P364 Take off contaminated clothing and wash it before reuse. P332+P313 If skin irritation occurs: Get medical advice/attention.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P363 Wash contaminated clothing before reuse.

P370+P378 In case of fire: Use for extinction: CO2, powder or water spray. P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P403+P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

#### Unknown acute toxicity:

0 % of the mixture consists of component(s) of unknown toxicity.

- · Classification system:
- NFPA ratings (scale 0 4)



Health = 1 Fire = 2 Reactivity = 0

### · HMIS-ratings (scale 0 - 4)



1 Health = 1 2 Fire = 2

REACTIVITY 0 Physical Hazard = 0

· Hazard(s) not otherwise classified (HNOC): None

## 3 Composition/Information on Ingredients

- · Chemical characterization: Mixtures
- Description: Mixture of substances listed below with non-hazardous additions.

· Dangerous Components:		
CAS: 64742-47-8	Distillates (petroleum), hydrotreated light	80-90%
	♦ Asp. Tox. 1, H304; ♦ Aquatic Chronic 2, H411; ♦ Skin Irrit. 2, H315; STOT SE 3, H336; Flam. Liq. 4, H227	
	d-limonene	10-20%
RTECS: GW 6360000	♦ Flam. Liq. 3, H226; ♦ Asp. Tox. 1, H304; ♦ Aquatic Acute 1, H400; Aquatic Chronic 1, H410; ♦ Skin Irrit. 2, H315; Skin Sens. 1, H317	

(Contd. on page 3)





OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 09/23/2019 Reviewed on 09/23/2019

Trade Name: Positron

 Part Number
 Packaging
 National Stock Number

 060-55
 55-Gal Drum
 6850-01-412-0028

 030-5
 5-Gal Pail
 6850-01-412-0026

 060-1
 4x1-Gal Case
 6850-01-411-8815

### 4 First-Aid Measures

- · Description of first aid measures
- · After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in the side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If swallowed and symptoms occur, consult a doctor.
- · Information for doctor
- · Most important symptoms and effects, both acute and delayed: No further relevant information available.
- Indication of any immediate medical attention and special treatment needed:

No further relevant information available.

## 5 Fire-Fighting Measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO<sub>2</sub>, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- For safety reasons unsuitable extinguishing agents: No further relevant information.
- · Special hazards arising from the substance or mixture: No further relevant information available.
- · Advice for firefighters
- · Special protective equipment for firefighters: No special measures required.

### 6 Accidental Release Measures

· Personal precautions, protective equipment and emergency procedures:

Wear protective equipment. Keep unprotected persons away.

Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.

Dilute with plenty of water.

Do not allow to enter sewers/surface or ground water.

· Methods and material for containment and cleaning up:

Absorb with liquid-binding material (i.e. sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

· Reference to other sections:

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

### 7 Handling and Storage

- · Handling
- · Precautions for safe handling:

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

(Contd. on page 4)



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 09/23/2019 Reviewed on 09/23/2019

Trade Name: Positron

 Part Number
 Packaging
 National Stock Number

 060-55
 55-Gal Drum
 6850-01-412-0028

 030-5
 5-Gal Pail
 6850-01-412-0026

 060-1
 4x1-Gal Case
 6850-01-411-8815

Protect against electrostatic charges.

- · Conditions for safe storage, including any incompatibilities
- · Storage
- · Requirements to be met by storerooms and receptacles: Store in the original container.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed.
- · Specific end use(s): No further relevant information available.

## 8 Exposure Controls/Personal Protection

- · Additional information about design of technical systems: No further data; see section 7.
- · Control parameters:
- · Components with occupational exposure limits:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

- · Additional information: The lists that were valid during the creation of this SDS were used as basis.
- · Exposure controls:
- Personal protective equipment
- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing and wash before reuse.

Wash hands before breaks and at the end of work.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

- · Breathing equipment: Not required.
- · Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Select glove material based on penetration times, rates of diffusion and degradation.

· Material of gloves:

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material cannot be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material:

The exact break-through time has to be determined and observed by the manufacturer of the protective gloves.

(Contd. on page 5)





OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 09/23/2019 Reviewed on 09/23/2019

Trade Name: Positron


 Part Number
 Packaging
 National Stock Number

 060-55
 55-Gal Drum
 6850-01-412-0028

 030-5
 5-Gal Pail
 6850-01-412-0026

 060-1
 4x1-Gal Case
 6850-01-411-8815

· Eye protection:



## 9 Physical and Chemical Properties

· Information on basic physical and chemical properties

· General Information

· Appearance:

Form: Liquid Color: Colorless

Odor: mild terpene odor
Odor threshold: Not determined.
pH-value: Not applicable.

· Change in condition

*Melting point/Melting range:* Not determined.

**Boiling point/Boiling range:** 348 °F • Flash point: 142 °F

· Flammability (solid, gaseous): Not applicable.

· Ignition temperature: 210 °C (410 210 °F)

Decomposition temperature: Not determined.Auto igniting: Not determined.

· Danger of explosion: Product is not explosive. However, formation of explosive air/vapor

mixtures are possible.

· Explosion limits:

 Lower:
 0.7 Vol %

 Upper:
 7.0 Vol %

· Vapor pressure @ 20 °C (6820 °F): 2.3 hPa (1.7 2.3 mm Hg)

• **Density @ 20 °C (6820 °F):** 0.807 g/cm³ (6.7344 0.807 lbs/gal)

Relative density:

Vapor density:
Evaporation rate @ 20 °C (6820 °F):
Not determined.
<1 (n-butyl acetate=1)</li>

· Solubility in / Miscibility with:

Water: Not miscible or difficult to mix.

· Partition coefficient (n-octanol/water): Not determined.

· Viscosity:

**Dynamic:** Not determined. **Kinematic:** Not determined.

(Contd. on page 6)





OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 09/23/2019 Reviewed on 09/23/2019

Trade Name: Positron

 Part Number
 Packaging
 National Stock Number

 060-55
 55-Gal Drum
 6850-01-412-0028

 030-5
 5-Gal Pail
 6850-01-412-0026

 060-1
 4x1-Gal Case
 6850-01-411-8815

· Solvent content:

*Organic solvents:* 100 % *VOC content:* 807 g/l

· Other information: No further relevant information available.

## 10 Stability and Reactivity

- · Reactivity: No further relevant information available.
- · Chemical stability: Stable under normal conditions.
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions: No dangerous reactions known.
- · Conditions to avoid: No further relevant information available.
- · Incompatible materials: No further relevant information available.
- Hazardous decomposition products: No dangerous decomposition products known.

### 11 Toxicological Information

- · Information on toxicological effects:
- · Acute toxicity:

LD/LC50 values that are relevant for classification:					
	64742-47-8 Distillates (petroleum), hydrotreated light				
	Oral	LD50	>5000 mg/kg (Rat)		
	Dermal	LD50	>2000 mg/kg (Rabbit)		
5989-27-5 d-limonene			monene		
	Oral	LD50	4400 mg/kg (Rat) Remarks: Behavioral: Change in motor activity (specific assay). Respiratory disorder Skin and Appendages: Other: Hair		

- · Primary irritant effect:
- · On the skin: Irritant to skin and mucous membranes.
- · On the eye: No irritating effect.
- · Sensitization: Sensitization possible through skin contact.
- Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

· Carcinogenic categories:

· IARC (International Agency for Research on Cancer):	
5989-27-5 d-limonene	3
· NTP (National Toxicology Program):	
None of the ingredients are listed.	
· OSHA-Ca (Occupational Safety & Health Administration):	
None of the ingredients are listed.	

(Contd. on page 7)





OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 09/23/2019 Reviewed on 09/23/2019

Trade Name: Positron

 Part Number
 Packaging
 National Stock Number

 060-55
 55-Gal Drum
 6850-01-412-0028

 030-5
 5-Gal Pail
 6850-01-412-0026

 060-1
 4x1-Gal Case
 6850-01-411-8815

### 12 Ecological Information

- · Toxicity:
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability: No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential: No further relevant information available.
- · Mobility in soil: No further relevant information available.
- · Ecotoxical effects:
- · Remark: Toxic for fish
- · Additional ecological information:
- · General notes:

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

- Results of PBT and vPvB assessment:
- · **PBT:** Not applicable.
- vPvB: Not applicable.
- · Other adverse effects: No further relevant information available.

### 13 Disposal Considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging
- · **Recommendation:** Disposal must be made according to official regulations.
- · Recommended cleansing agent: Water, if necessary with cleansing agents.

### 14 Transport Information

· UN-Number:

· DOT, ADR/ADN, ADN, IMDG, IATA Non-Regulated Material

· UN proper shipping name:

· DOT, ADR/ADN, ADN, IMDG, IATA Non-Regulated Material

· Transport hazard class(es):

· DOT, ADR/ADN, IMDG, IATA

· Class: Non-Regulated Material

· Label:

· ADN/R Class: Non-Regulated Material

· Packing group:

· DOT, ADR/ADN, IMDG, IATA Non-Regulated Material

Environmental hazards:
 Special precautions for user:
 Not applicable.

Transport in bulk according to Annex II of

MARPOL73/78 and the IBC Code: Not applicable.

(Contd. on page 8)





OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 09/23/2019 Reviewed on 09/23/2019

Trade Name: Positron

 Part Number
 Packaging
 National Stock Number

 060-55
 55-Gal Drum
 6850-01-412-0028

 030-5
 5-Gal Pail
 6850-01-412-0026

 060-1
 4x1-Gal Case
 6850-01-411-8815

· **UN "Model Regulation":** Non-Regulated Material

## 15 Regulatory Information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture:
- SARA (Superfund Amendments and Reauthorization):
- · Section 355 (extremely hazardous substances):

None of the ingredients are listed.

· Section 313 (Specific toxic chemical listings):

None of the ingredients are listed.

· TSCA (Toxic Substances Control Act):

64742-47-8 Distillates (petroleum), hydrotreated light

5989-27-5 d-limonene

- · California Proposition 65:
- · Chemicals known to cause cancer:

None of the ingredients are listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients are listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients are listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients are listed.

- · Carcinogenic categories:
- · EPA (Environmental Protection Agency):

None of the ingredients are listed.

· TLV (Threshold Limit Value established by ACGIH):

None of the ingredients are listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health):

None of the ingredients are listed.

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

Hazard pictograms:





- · Signal word: Danger
- · Hazard-determining components of labeling:

Distillates (petroleum), hydrotreated light

d-limonene





OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 09/23/2019 Reviewed on 09/23/2019

Trade Name: Positron

 Part Number
 Packaging
 National Stock Number

 060-55
 55-Gal Drum
 6850-01-412-0028

 030-5
 5-Gal Pail
 6850-01-412-0026

 060-1
 4x1-Gal Case
 6850-01-411-8815

#### · Hazard statements:

H227 Combustible liquid.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H336 May cause drowsiness or dizziness.

H304 May be fatal if swallowed and enters airways.

### Precautionary statements:

P210 Keep away from flames and hot surfaces. – No smoking.

P261 Avoid breathing dust/fume/gas/mist/vapors/spray.

P264 Wash thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P272 Contaminated work clothing must not be allowed out of the workplace.
P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301+P310 If swallowed: Immediately call a poison center/doctor.

P321 Specific treatment (see supplementary first aid instructions on this Safety Data Sheet).

P331 Do NOT induce vomiting.

P302+P352 If on skin: Wash with plenty of water.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P312 Call a poison center/doctor if you feel unwell.

P362+P364 Take off contaminated clothing and wash it before reuse.

P332+P313 If skin irritation occurs: Get medical advice/attention.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P363 Wash contaminated clothing before reuse.

P370+P378 In case of fire: Use for extinction: CO2, powder or water spray.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P403+P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

#### · National regulations:

None of the ingredients are listed.

Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### 16 Other Information

The information and recommendations in this safety data sheet are, to the best of our knowledge, accurate as of the date of issue. Nothing herein shall be deemed to create warranty, expressed or implied, and shall not establish a legally valid contractual relationship. It is the responsibility of the user to determine applicability of this information and the suitability of the material or product for any particular purpose.

### · Date of last revision/ revision number: 09/23/2019 / 2

#### · Abbreviations and acronyms:

ADR: The European Agreement concerning the International Carriage of Dangerous Goods by Road

ADN: The European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)





OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 09/23/2019 Reviewed on 09/23/2019

Trade Name: Positron

Part Number National Stock Number Packaging 060-55 55-Gal Drum 6850-01-412-0028 5-Gal Pail 030-5 6850-01-412-0026 6850-01-411-8815 060-1 4x1-Gal Case

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, ÉU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety and Health

OSHA: Occupational Safety & Health Administration

TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit

Flam. Liq. 3: Flammable liquids – Category 3 Flam. Liq. 4: Flammable liquids – Category 4 Skin Irrit. 2: Skin corrosion/irritation - Category 2 Skin Sens. 1: Skin sensitisation - Category 1

STOT SE 3: Specific target organ toxicity (single exposure) - Category 3

Asp. Tox. 1: Aspiration hazard – Category 1
Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1 Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

\* Data compared to the previous version altered.

SDS created by MSDS Authoring Services www.msdsauthoring.com +1-877-204-9106