

### SECTION 1: Identification

#### 1.1. Identification

Product form	: Substance
Substance name	: Methanol
CAS-No.	: 67-56-1
Formula	: CH4O
Synonyms	: Methyl Alcohol

#### 1.2. Recommended use and restrictions on use

Use of the substance/mixture	: Solvent
------------------------------	-----------

#### 1.3. Supplier

##### **ECOLINK**

2177 Flintstone Drive  
Suite A  
Tucker, GA 30084  
770-621-8240 (t)  
[www.ecolink.com](http://www.ecolink.com)

#### 1.4. Emergency telephone number

Emergency number	: INFOTRAC 800-535-5053
------------------	-------------------------

### SECTION 2: Hazard(s) identification

#### 2.1. Classification of the substance or mixture

##### GHS-US classification

Flammable liquids Category 2	H225	Highly flammable liquid and vapor
Acute toxicity (oral) Category 3	H301	Toxic if swallowed
Acute toxicity (dermal) Category 3	H311	Toxic in contact with skin
Acute toxicity (inhalation:dust,mist) Category 3	H331	Toxic if inhaled
Specific target organ toxicity (single exposure) Category 1	H370	Causes damage to organs (eyes, Skin, respiratory system, central nervous system, digestive system) (oral)

Full text of H statements : see section 16

#### 2.2. GHS Label elements, including precautionary statements

##### GHS-US labeling

Hazard pictograms (GHS-US)



Signal word (GHS-US)

: Danger

Hazard statements (GHS-US)

: H225 - Highly flammable liquid and vapor  
H301+H311+H331 - Toxic if swallowed, in contact with skin or if inhaled  
H370 - Causes damage to organs (eyes, Skin, respiratory system, central nervous system, digestive system) (oral)

Precautionary statements (GHS-US)

: P210 - Keep away from heat, sparks, open flames, hot surfaces. - No smoking  
P233 - Keep container tightly closed  
P240 - Ground/Bond container and receiving equipment  
P241 - Use explosion-proof ventilating, lighting, electrical equipment  
P242 - Use only non-sparking tools  
P243 - Take precautionary measures against static discharge  
P260 - Do not breathe fume, mist, vapors, spray

# Methanol

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P261 - Avoid breathing dust, fume, gas, mist, spray, vapors  
P264 - Wash hands thoroughly after handling  
P270 - Do not eat, drink or smoke when using this product  
P271 - Use only outdoors or in a well-ventilated area  
P280 - Wear protective gloves, protective clothing, eye protection, face protection  
P301+P310 - If swallowed: Immediately call a POISON CENTER or doctor/physician  
P302+P352 - If on skin: Wash with plenty of Remove immediately contaminated clothing  
P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower  
P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing  
P307+P311 - If exposed: Call a poison center/doctor  
P311 - Call a POISON CENTER or doctor/physician  
P312 - Call a POISON CENTER or doctor/physician if you feel unwell  
P330 - Rinse mouth  
P361 - Take off immediately all contaminated clothing  
P363 - Wash contaminated clothing before reuse  
P370+P378 - In case of fire: Use water fog, foam, dry chemical or carbon dioxide (CO2) to extinguish  
P403+P233 - Store in a well-ventilated place. Keep container tightly closed  
P403+P235 - Store in a well-ventilated place. Keep cool  
P405 - Store locked up  
P501 - Dispose of contents/container in accordance with local, regional, national, and/or international regulations.

### 2.3. Other hazards which do not result in classification

No additional information available

### 2.4. Unknown acute toxicity (GHS US)

Not applicable

## SECTION 3: Composition/Information on ingredients

### 3.1. Substances

Substance type : Mono-constituent

Name	Product identifier	%	GHS-US classification
Methanol (Main constituent)	(CAS-No.) 67-56-1	100	Flam. Liq. 2, H225 Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Inhalation:dust,mist), H331 STOT SE 1, H370

Full text of hazard classes and H-statements : see section 16

### 3.2. Mixtures

Not applicable

## SECTION 4: First-aid measures

### 4.1. Description of first aid measures

First-aid measures general : Call a physician immediately.  
First-aid measures after inhalation : Remove the victim into fresh air. Immediately consult a doctor/medical service.  
First-aid measures after skin contact : Wash immediately with lots of water. Soap may be used. Do not apply (chemical) neutralizing agents. Remove clothing before washing. Consult a doctor/medical service.  
First-aid measures after eye contact : Remove contact lenses, if present and easy to do. Continue rinsing. Rinse with water. Take victim to an ophthalmologist if irritation persists.  
First-aid measures after ingestion : Rinse mouth with water. Give nothing to drink. Do not induce vomiting. Immediately consult a doctor/medical service. Call Poison Control Center. Ingestion of large quantities: immediately to hospital. Take the container/vomit to the doctor/hospital. Doctor: administration of chemical antidote. Doctor: gastric lavage.

### 4.2. Most important symptoms and effects (acute and delayed)

Potential Adverse human health effects and symptoms : Causes damage to organs (central nervous system, eyes (blindness)). Odour threshold is well above the exposure limit. Produces effects on the nervous system. Toxic if swallowed. Toxic in contact with skin. Slightly irritant to skin. Toxic if inhaled. Slightly irritant to respiratory organs. Slightly irritant to eyes. Caution! Substance is absorbed through the skin.  
Symptoms/effects after inhalation : Slight irritation. EXPOSURE TO HIGH CONCENTRATIONS: Coughing. Symptoms similar to those listed under ingestion.  
Symptoms/effects after skin contact : Symptoms similar to those listed under ingestion. Slight irritation.  
Symptoms/effects after eye contact : Redness of the eye tissue. Lacrimation.

# Methanol

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Symptoms/effects after ingestion	: Nausea. Vomiting. AFTER INGESTION OF HIGH QUANTITIES: FOLLOWING SYMPTOMS MAY APPEAR LATER: Change in the haemogramme/blood composition. Headache. Feeling of weakness. Abdominal pain. Muscular pain. Central nervous system depression. Dizziness. Mental confusion. Drunkenness. Coordination disorders. Disturbed motor response. Disturbances of consciousness. Visual disturbances. Blindness. Respiratory difficulties. Cramps/uncontrolled muscular contractions.
Chronic symptoms	: ON CONTINUOUS/REPEATED EXPOSURE/CONTACT: Red skin. Dry skin. Skin rash/inflammation. Headache. Disturbed tactile sensibility. Visual disturbances. Sleeplessness. Gastrointestinal complaints. Cardiac and blood circulation effects.

### 4.3. Immediate medical attention and special treatment, if necessary

Hospitalize at once. Until victim can be cared for by specialized staff:

## SECTION 5: Fire-fighting measures

### 5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media	: Quick-acting ABC powder extinguisher. Quick-acting BC powder extinguisher. Quick-acting class B foam extinguisher. Quick-acting CO2 extinguisher. Class B foam (alcohol-resistant). Water spray if puddle cannot expand.
Unsuitable extinguishing media	: Water (quick-acting extinguisher, reel); risk of puddle expansion. Water; risk of puddle expansion.

### 5.2. Specific hazards arising from the chemical

Fire hazard	: DIRECT FIRE HAZARD: Highly flammable liquid and vapour. Gas/vapor flammable with air within explosion limits. INDIRECT FIRE HAZARD: May be ignited by sparks.
Explosion hazard	: DIRECT EXPLOSION HAZARD: Gas/vapour explosive with air within explosion limits. INDIRECT EXPLOSION HAZARD: may be ignited by sparks. Reactions with explosion hazards: see "Reactivity Hazard".
Reactivity	: Violent to explosive reaction with (some) metal powders and with (strong) oxidizers. Violent exothermic reaction with (some) acids and with (some) halogens compounds.

### 5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions	: Cool tanks/drums with water spray/remove them into safety. Do not move the load if exposed to heat. Take account of toxic fire-fighting water. Use water moderately and if possible collect or contain it.
Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

#### 6.1.1. For non-emergency personnel

Protective equipment	: Gas-tight suit.
Emergency procedures	: Keep upwind. Mark the danger area. Consider evacuation. Close doors and windows of adjacent premises. Stop engines and no smoking. No naked flames or sparks. Spark- and explosionproof appliances and lighting equipment. Keep containers closed. Wash contaminated clothes.

#### 6.1.2. For emergency responders

Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
----------------------	---

### 6.2. Environmental precautions

Prevent soil and water pollution. Prevent spreading in sewers.

### 6.3. Methods and material for containment and cleaning up

For containment	: Contain released product, pump into suitable containers. Plug the leak, cut off the supply. Dam up the liquid spill. Try to reduce evaporation. Measure the concentration of the explosive gas-air mixture. Dilute combustible/toxic gases/vapors with water spray. Take account of toxic/corrosive precipitation water. Provide equipment/receptacles with earthing. Do not use compressed air for pumping over spills.
Methods for cleaning up	: Take up liquid spill into a non combustible material e.g.: sand, earth, vermiculite slaked lime or soda ash. Scoop absorbed substance into closing containers. Carefully collect the spill/leftovers. Damaged/cooled tanks must be emptied. Do not use compressed air for pumping over spills. Clean contaminated surfaces with an excess of water. Take collected spill to manufacturer/competent authority. Wash clothing and equipment after handling.
Other information	: Dispose of materials or solid residues at an authorized site.

# Methanol

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 6.4. Reference to other sections

For further information refer to section 13.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

- Precautions for safe handling : Use spark-/explosionproof appliances and lighting system. Take precautions against electrostatic charges. Keep away from naked flames/heat. Keep away from ignition sources/sparks. Measure the concentration in the air regularly. Work under local exhaust/ventilation. Comply with the legal requirements. Remove contaminated clothing immediately. Clean contaminated clothing. Handle uncleaned empty containers as full ones. Thoroughly clean/dry the installation before use. Do not discharge the waste into the drain. Do not use compressed air for pumping over.
- Hygiene measures : Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

### 7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Ground/bond container and receiving equipment.
- Storage conditions : Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up. This material is a static accumulator. Use non-sparking tools. Store in a cool, dry, well-ventilated area, away from incompatible substances. Store only in approved properly labeled containers. Containers should be grounded and bonded.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

Methanol (67-56-1)		
ACGIH	ACGIH TWA (ppm)	200 ppm
ACGIH	ACGIH STEL (ppm)	250 ppm

### 8.2. Appropriate engineering controls

- Appropriate engineering controls : Ensure good ventilation of the work station.
- Environmental exposure controls : Avoid release to the environment.

### 8.3. Individual protection measures/Personal protective equipment

#### Materials for protective clothing:

GIVE GOOD RESISTANCE: polyethylene/ethylenevinylalcohol. styrene-butadiene rubber. viton.  
GIVE LESS RESISTANCE: chloroprene rubber. chlorinated polyethylene. natural rubber. nitrile rubber/PVC.  
GIVE POOR RESISTANCE: leather. neoprene. nitrile rubber. polyethylene. PVA. PVC. polyurethane

#### Hand protection:

Gloves

#### Eye protection:

Safety glasses

#### Skin and body protection:

Head/neck protection. Protective clothing

#### Respiratory protection:

Full face mask with filter type A at conc. in air > exposure limit. High vapour/gas concentration: self-contained respirator

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

- Physical state : Liquid
- Appearance : Liquid.
- Color : Colourless
- Odor : Alcohol odor

# Methanol

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Odor threshold	: 4.2 - 8940 ppm 5.59 - 11890 mg/m <sup>3</sup>
pH	: No data available
Melting point	: -97.8 °C
Freezing point	: No data available
Boiling point	: 64.7 °C (148.5 °F)
Critical temperature	: 240 °C
Critical pressure	: 79547 hPa
Flash point	: 9.7 °C (Closed cup, 1013 hPa) (49.5 °F)
Relative evaporation rate (butyl acetate=1)	: 4.1
Relative evaporation rate (ether=1)	: 6.3
Flammability (solid, gas)	: Not applicable.
Vapor pressure	: 98 mmHg
Vapor pressure at 50 °C	: 552 hPa
Relative vapor density at 20 °C	: 1.1
Relative density	: 0.79 - 0.80 (20 °C)
Relative density of saturated gas/air mixture	: 1
Specific gravity / density	: 790 - 800 kg/m <sup>3</sup> (20 °C)
Molecular mass	: 32.04 g/mol
Solubility	: Miscible
Log Pow	: -0.77 (Experimental value)
Auto-ignition temperature	: 455 °C (1013 hPa) (851 °F)
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: 0.544 - 0.59 mPa.s (25 °C)
Explosion limits	: 5.5 - 36.5 vol % LEL: 5.5 vol % UEL: 36.5 vol %
Explosive properties	: No data available
Oxidizing properties	: No data available

### 9.2. Other information

Minimum ignition energy	: 0.14 mJ
Saturation concentration	: 166 g/m <sup>3</sup>
VOC content	: 100 %
Other properties	: Clear. Hygroscopic. Volatile. Substance has neutral reaction.

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Violent to explosive reaction with (some) metal powders and with (strong) oxidizers. Violent exothermic reaction with (some) acids and with (some) halogens compounds.

### 10.2. Chemical stability

Hygroscopic.

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

### 10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

### 10.5. Incompatible materials

Acid chlorides, acid anhydrides, oxidizing agents, alkalis metals, reducing agents, acids.

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

# Methanol

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Acute toxicity : Oral: Toxic if swallowed. Dermal: Toxic in contact with skin. Inhalation:dust,mist: Toxic if inhaled.

<b>Methanol (67-56-1)</b>	
LD50 oral rat	1187 - 2769 mg/kg body weight (BASF test, Rat, Male/female, Weight of evidence)
LD50 dermal rabbit	17100 mg/kg (Rabbit, Inconclusive, insufficient data)
LC50 inhalation rat (mg/l)	128.2 mg/l air (BASF test, 4 h, Rat, Male/female, Weight of evidence)
ATE US (oral)	100 mg/kg body weight
ATE US (dermal)	300 mg/kg body weight
ATE US (gases)	64000 ppmV/4h
ATE US (vapors)	85 mg/l/4h
ATE US (dust, mist)	0.5 mg/l/4h

Skin corrosion/irritation : Not classified

Serious eye damage/irritation : Not classified

Respiratory or skin sensitization : Not classified

Germ cell mutagenicity : Not classified

Carcinogenicity : Not classified

Reproductive toxicity : Not classified

Specific target organ toxicity – single exposure : Causes damage to organs (eyes, Skin, respiratory system, central nervous system, digestive system) (oral).

Specific target organ toxicity – repeated exposure : Not classified

Aspiration hazard : Not classified

Potential Adverse human health effects and symptoms : Causes damage to organs (central nervous system, eyes (blindness)). Odour threshold is well above the exposure limit. Produces effects on the nervous system. Toxic if swallowed. Toxic in contact with skin. Slightly irritant to skin. Toxic if inhaled. Slightly irritant to respiratory organs. Slightly irritant to eyes. Caution! Substance is absorbed through the skin.

Symptoms/effects after inhalation : Slight irritation. EXPOSURE TO HIGH CONCENTRATIONS: Coughing. Symptoms similar to those listed under ingestion.

Symptoms/effects after skin contact : Symptoms similar to those listed under ingestion. Slight irritation.

Symptoms/effects after eye contact : Redness of the eye tissue. Lacrimation.

Symptoms/effects after ingestion : Nausea. Vomiting. AFTER INGESTION OF HIGH QUANTITIES: FOLLOWING SYMPTOMS MAY APPEAR LATER: Change in the haemogramme/blood composition. Headache. Feeling of weakness. Abdominal pain. Muscular pain. Central nervous system depression. Dizziness. Mental confusion. Drunkenness. Coordination disorders. Disturbed motor response. Disturbances of consciousness. Visual disturbances. Blindness. Respiratory difficulties. Cramps/uncontrolled muscular contractions.

Chronic symptoms : ON CONTINUOUS/REPEATED EXPOSURE/CONTACT: Red skin. Dry skin. Skin rash/inflammation. Headache. Disturbed tactile sensibility. Visual disturbances. Sleeplessness. Gastrointestinal complaints. Cardiac and blood circulation effects.

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - water : Not harmful to crustacea. Not harmful to fishes. Groundwater pollutant. Inhibition of activated sludge. Not harmful to algae. Not harmful to bacteria.

<b>Methanol (67-56-1)</b>	
LC50 fish 1	15400 mg/l (EPA 660/3 - 75/009, 96 h, Lepomis macrochirus, Flow-through system, Fresh water, Experimental value)
EC50 Daphnia 1	18260 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 96 h, Daphnia magna, Semi-static system, Fresh water, Experimental value)
ErC50 (algae)	22000 mg/l (OECD 201: Alga, Growth Inhibition Test, 96 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value)

### 12.2. Persistence and degradability

<b>Methanol (67-56-1)</b>	
Persistence and degradability	Biodegradable in the soil. Readily biodegradable in water.
Biochemical oxygen demand (BOD)	0.6 - 1.12 g O <sub>2</sub> /g substance
Chemical oxygen demand (COD)	1.42 g O <sub>2</sub> /g substance

# Methanol

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Methanol (67-56-1)	
ThOD	1.5 g O <sub>2</sub> /g substance

### 12.3. Bioaccumulative potential

Methanol (67-56-1)	
BCF fish 1	1 - 4.5 (72 h, Cyprinus carpio, Static system, Fresh water, Experimental value)
Log Pow	-0.77 (Experimental value)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).

### 12.4. Mobility in soil

Methanol (67-56-1)	
Surface tension	0.023 N/m (20 °C)
Log Koc	-0.89 - -0.21 (log Koc, Calculated value)
Ecology - soil	Highly mobile in soil.

### 12.5. Other adverse effects

No additional information available

## SECTION 13: Disposal considerations

### 13.1. Disposal methods

- Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.
- Product/Packaging disposal recommendations : Do not discharge into drains or the environment. Remove waste in accordance with local and/or national regulations. Hazardous waste shall not be mixed together with other waste. Different types of hazardous waste shall not be mixed together if this may entail a risk of pollution or create problems for the further management of the waste. Hazardous waste shall be managed responsibly. All entities that store, transport or handle hazardous waste shall take the necessary measures to prevent risks of pollution or damage to people or animals. Recycle by distillation. Incinerate under surveillance with energy recovery. Obtain the consent of pollution control authorities before discharging to wastewater treatment plants.

## SECTION 14: Transport information

### Department of Transportation (DOT)

In accordance with DOT

- Transport document description : UN1230 Methanol, 3, II
- UN-No.(DOT) : UN1230
- Proper Shipping Name (DOT) : Methanol
- Class (DOT) : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120
- Packing group (DOT) : II - Medium Danger
- Hazard labels (DOT) : 3 - Flammable liquid



- DOT Packaging Non Bulk (49 CFR 173.xxx) : 202
- DOT Packaging Bulk (49 CFR 173.xxx) : 242
- DOT Symbols : D - Proper shipping name for domestic use only, or to and from Canada



# Methanol

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

DOT Special Provisions (49 CFR 172.102)	: IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized. T7 - 4 178.274(d)(2) Normal..... 178.275(d)(3) TP2 - a. The maximum degree of filling must not exceed the degree of filling determined by the following: (image) Where: tr is the maximum mean bulk temperature during transport, tf is the temperature in degrees celsius of the liquid during filling, and a is the mean coefficient of cubical expansion of the liquid between the mean temperature of the liquid during filling (tf) and the maximum mean bulk temperature during transportation (tr) both in degrees celsius. b. For liquids transported under ambient conditions may be calculated using the formula: (image) Where: d15 and d50 are the densities (in units of mass per unit volume) of the liquid at 15 C (59 F) and 50 C (122 F), respectively.
DOT Packaging Exceptions (49 CFR 173.xxx)	: 150
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	: 1 L
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	: 60 L
DOT Vessel Stowage Location	: B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this section is exceeded.
DOT Vessel Stowage Other	: 40 - Stow "clear of living quarters"
Other information	: No supplementary information available.

### Transportation of Dangerous Goods

#### Transport by sea

Transport document description (IMDG)	: UN 1230 Methanol, 3 (6.1), II
UN-No. (IMDG)	: 1230
Proper Shipping Name (IMDG)	: Methanol
Class (IMDG)	: 3 - Flammable liquids
Packing group (IMDG)	: II - substances presenting medium danger
Subsidiary risks (IMDG)	: 6.1 - Toxic substances
EmS-No. (1)	: F-E
EmS-No. (2)	: S-D
MFAG-No	: 19

#### Air transport

Transport document description (IATA)	: UN 1230 Methanol, 3 (6.1), II
UN-No. (IATA)	: 1230
Proper Shipping Name (IATA)	: Methanol
Class (IATA)	: 3 - Flammable Liquids
Packing group (IATA)	: II - Medium Danger
Subsidiary risks (IATA)	: 6.1 - Toxic substances

## SECTION 15: Regulatory information

### 15.1. US Federal regulations

Methanol (67-56-1)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory Subject to reporting requirements of United States SARA Section 313	
CERCLA RQ	5000 lb
SARA Section 311/312 Hazard Classes	Physical hazard - Flammable Health hazard - Acute Health hazard - Chronic

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory



# Methanol

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.

Methanol	CAS-No. 67-56-1	100%
----------	-----------------	------

### 15.2. International regulations

#### CANADA

No additional information available

#### EU-Regulations

No additional information available

#### National regulations

No additional information available

### 15.3. US State regulations

Methanol (67-56-1)	
U.S. - California - Proposition 65 - Carcinogens List	No
U.S. - California - Proposition 65 - Developmental Toxicity	Yes
U.S. - California - Proposition 65 - Reproductive Toxicity - Female	No
U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No
State or local regulations	U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List

**⚠ WARNING** This product can expose you to Methanol, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

## SECTION 16: Other information

Revision date : 05/02/2018


Full text of H-phrases:

H225	Highly flammable liquid and vapor
H301	Toxic if swallowed
H311	Toxic in contact with skin
H331	Toxic if inhaled
H370	Causes damage to organs

NFPA health hazard : 2 - Materials that, under emergency conditions, can cause temporary incapacitation or residual injury.

NFPA fire hazard : 3 - Liquids and solids (including finely divided suspended solids) that can be ignited under almost all ambient temperature conditions.

NFPA reactivity : 0 - Material that in themselves are normally stable, even under fire conditions.



SDS US (GHS HazCom 2012)

*The information above is believed to be accurate and represents the best information currently available to us. However, we make no warranty of merchantability or any other warranty, express or implied, with respect to such information, and we assume no liability resulting from its use. Users should make their own investigations to determine the suitability of the information for their particular purposes. Please be advised revisions to the Safety Data Sheet (SDS) may require a label update. In no event shall ECOLINK be liable for any claims, losses, or damages of any third party or for lost profits or any special, indirect, incidental, consequential or exemplary damages, howsoever arising, even if ECOLINK has been advised of the possibility of such damages. The vendor assumes no responsibility for injury or damages resulting from the inappropriate alteration or manipulation of this SDS and its contents from that originally submitted by ECOLINK.*