

SECTION 1: Identification

1.1. Identification

Product form	: Mixture
Product name	: Mineral Spirits (Regular)
CAS-No.	: 8052-41-3
Synonyms	: Low boiling point naphtha - unspecified / Stoddard solvent
BIG no	: F07604

1.2. Recommended use and restrictions on use

Recommended use	: Consumer uses: Private households (= general public = consumers)
Restrictions on use	: None known

1.3. Supplier

ECOLINK

2177 Flintstone Drive
Suite A
Tucker, GA 30084
770-621-8240 (t)
www.ecolink.com

1.4. Emergency telephone number

Emergency number : **INFOTRAC** 800-535-5053

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS-US classification

Flammable liquids Category 3	H226	Flammable liquid and vapor
Serious eye damage/eye irritation Category 2A	H319	Causes serious eye irritation
Reproductive toxicity Category 1B	H360	May damage fertility or the unborn child
Specific target organ toxicity (single exposure) Category 3	H336	May cause drowsiness or dizziness
Specific target organ toxicity (repeated exposure) Category 2	H373	May cause damage to organs through prolonged or repeated exposure
Aspiration hazard Category 1	H304	May be fatal if swallowed and enters airways

Full text of H statements : see section 16

2.2. GHS Label elements, including precautionary statements

GHS-US labeling

Hazard pictograms (GHS-US) :



Signal word (GHS-US) :

Danger

Hazard statements (GHS-US) :

H226 - Flammable liquid and vapor
H304 - May be fatal if swallowed and enters airways
H319 - Causes serious eye irritation
H336 - May cause drowsiness or dizziness
H360 - May damage fertility or the unborn child
H373 - May cause damage to organs through prolonged or repeated exposure

Precautionary statements (GHS-US) :

P201 - Obtain special instructions before use
P202 - Do not handle until all safety precautions have been read and understood
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

Mineral Spirits (Regular)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

smoking heat, sparks, open flames, hot surfaces
P233 - Keep container tightly closed
P240 - Ground/Bond container and receiving equipment
P241 - Use explosion-proof electrical, ventilating, lighting equipment
P242 - Use only non-sparking tools
P243 - Take precautionary measures against static discharge
P260 - Do not breathe vapors, mist, spray
P261 - Avoid breathing mist, vapors
P264 - Wash Skin thoroughly after handling
P271 - Use only outdoors or in a well-ventilated area
P280 - Wear protective gloves, eye protection, face protection
P301+P310 - If swallowed: Immediately call a POISON CENTER or doctor/physician.
P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower
P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing
P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P308+P313 - If exposed or concerned: Get medical advice/attention
P312 - Call a POISON CENTER or doctor/physician. if you feel unwell
P314 - Get medical advice/attention if you feel unwell
P331 - Do NOT induce vomiting
P337+P313 - If eye irritation persists: Get medical advice/attention
P370+P378 - In case of fire: Use water fog, foam, dry chemical or carbon dioxide (CO2) to extinguish
P403+P233 - Store in a well-ventilated place. Keep container tightly closed
P403+P235 - Store in a well-ventilated place. Keep cool
P405 - Store locked up
P501 - Dispose of contents/container in accordance with local, regional, national, and/or international regulations.

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	GHS-US classification
Stoddard Solvent	(CAS-No.) 8052-41-3	< 95	Flam. Liq. 3, H226 Eye Irrit. 2A, H319 Muta. 1B, H340 Carc. 1B, H350 Repr. 1B, H360 STOT SE 3, H336 STOT RE 2, H373 Asp. Tox. 1, H304
Pseudocumene	(CAS-No.) 95-63-6	5.14	Flam. Liq. 3, H226 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 STOT SE 3, H335 Aquatic Chronic 2, H411

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures general : Call a physician immediately.
First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact : Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing.
First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion : Do not induce vomiting. Call a physician immediately.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects : May cause drowsiness or dizziness.

Mineral Spirits (Regular)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Symptoms/effects after eye contact : Eye irritation.
Symptoms/effects after ingestion : Risk of lung edema.

4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media : Water (quick-acting extinguisher, reel); risk of puddle expansion. Water; risk of puddle expansion.

5.2. Specific hazards arising from the chemical

Fire hazard : Flammable liquid and vapor.
Reactivity : Flammable liquid and vapor.

5.3. Special protective equipment and precautions for fire-fighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : No open flames, no sparks, and no smoking. Only qualified personnel equipped with suitable protective equipment may intervene. Do not breathe dust/fume/gas/mist/vapors/spray.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment. Notify authorities if product enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.
Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapors may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapors/spray. Use only outdoors or in a well-ventilated area. Avoid contact with skin and eyes.
Hygiene measures : Separate working clothes from town clothes. Launder separately. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Ground/bond container and receiving equipment.
Storage conditions : Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Mineral Spirits (Regular) (8052-41-3)		
ACGIH	Local name	Stoddard solvent
ACGIH	ACGIH TWA (ppm)	100 ppm
ACGIH	Remark (ACGIH)	Eye, skin, & kidney dam;

Mineral Spirits (Regular)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Mineral Spirits (Regular) (8052-41-3)		
OSHA	OSHA PEL (TWA) (mg/m ³)	2900 mg/m ³
OSHA	OSHA PEL (TWA) (ppm)	500 ppm
Pseudocumene (95-63-6)		
ACGIH	ACGIH TWA (ppm)	25 ppm
Stoddard Solvent (8052-41-3)		
ACGIH	Local name	Stoddard solvent
ACGIH	ACGIH TWA (ppm)	100 ppm
ACGIH	Remark (ACGIH)	Eye, skin, & kidney dam;
OSHA	OSHA PEL (TWA) (mg/m ³)	2900 mg/m ³
OSHA	OSHA PEL (TWA) (ppm)	500 ppm

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.
Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Hand protection:

Protective gloves

Eye protection:

Safety glasses

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

Wear respiratory protection

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid
Appearance : Liquid.
Color : Colourless
Odor : Petroleum-like odour
Odor threshold : 0.9 ppm
5.1 mg/m³
pH : No data available
Melting point : Not applicable
Freezing point : No data available
Boiling point : 159 - 195 °C
Flash point : 38 - 60 °C
Relative evaporation rate (butyl acetate=1) : No data available
Flammability (solid, gas) : Not applicable.
Vapor pressure : 2.85 hPa (20 °C)
Relative vapor density at 20 °C : No data available
Relative density : 0.79 (15 °C)
Solubility : Water: insoluble
Ethanol: soluble
Ether: soluble
Log Pow : 3.16 - 7.06
Auto-ignition temperature : 260 °C

Mineral Spirits (Regular)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Decomposition temperature	: No data available
Viscosity, kinematic	: 1.2 mm ² /s (25 °C)
Viscosity, dynamic	: No data available
Explosion limits	: 0.8 - 5.6 vol % LEL: 0.8 vol % UEL: 5.6 vol %
Explosive properties	: No data available
Oxidizing properties	: No data available

9.2. Other information

Other properties : Clear.

SECTION 10: Stability and reactivity

10.1. Reactivity

Flammable liquid and vapor.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

Pseudocumene (95-63-6)	
LD50 oral rat	6000 mg/kg body weight (EU Method B.1 tris: Acute oral toxic – Acute toxic class method, Rat, Male, Experimental value)
LD50 dermal rat	3440 mg/kg (OECD 402: Acute Dermal Toxicity, 24 h, Rat, Male/female, Read-across)
LC50 inhalation rat (mg/l)	10.2 mg/l air (Other, 4 h, Rat, Male/female, Read-across)
ATE US (gases)	4500 ppmV/4h
ATE US (vapors)	18 mg/l/4h
ATE US (dust, mist)	1.5 mg/l/4h

Stoddard Solvent (8052-41-3)	
LD50 oral rat	> 6500 mg/kg (Rat)
Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified.
Carcinogenicity	: Not classified
Reproductive toxicity	: May damage fertility or the unborn child.
Specific target organ toxicity – single exposure	: May cause drowsiness or dizziness.

Pseudocumene (95-63-6)	
Specific target organ toxicity – single exposure	May cause respiratory irritation.

Stoddard Solvent (8052-41-3)	
Specific target organ toxicity – single exposure	May cause drowsiness or dizziness.

Mineral Spirits (Regular)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Specific target organ toxicity – repeated exposure : May cause damage to organs through prolonged or repeated exposure.

Stoddard Solvent (8052-41-3)

Specific target organ toxicity – repeated exposure	May cause damage to organs through prolonged or repeated exposure.
--	--

Aspiration hazard : May be fatal if swallowed and enters airways.

Viscosity, kinematic : 1.2 mm²/s (25 °C)

Symptoms/effects : May cause drowsiness or dizziness.

Symptoms/effects after eye contact : Eye irritation.

Symptoms/effects after ingestion : Risk of lung edema.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms or to cause long-term adverse effects in the environment.

Pseudocumene (95-63-6)

LC50 fish 1	7.72 mg/l (96 h, Pimephales promelas, Flow-through system, Fresh water, Experimental value)
-------------	---

12.2. Persistence and degradability

Pseudocumene (95-63-6)

Persistence and degradability	Biodegradable in the soil. Not readily biodegradable in water.
-------------------------------	--

Chemical oxygen demand (COD)	0.44 g O ₂ /g substance
------------------------------	------------------------------------

Stoddard Solvent (8052-41-3)

Persistence and degradability	No (test)data on mobility of the components available.
-------------------------------	--

12.3. Bioaccumulative potential

Mineral Spirits (Regular) (8052-41-3)

Log Pow	3.16 - 7.06
---------	-------------

Pseudocumene (95-63-6)

BCF fish 1	31 - 275 (Other, 8 week(s), Cyprinus carpio, Weight of evidence)
------------	--

Log Pow	3.63 - 4.09 (Experimental value)
---------	----------------------------------

Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).
---------------------------	--

Stoddard Solvent (8052-41-3)

Bioaccumulative potential	No test data of component(s) available.
---------------------------	---

12.4. Mobility in soil

Mineral Spirits (Regular) (8052-41-3)

Log Koc	2.85 - 6.74 (log Koc)
---------	-----------------------

Pseudocumene (95-63-6)

Surface tension	0.029 N/m
-----------------	-----------

Log Koc	3.04 (log Koc, Calculated value)
---------	----------------------------------

Ecology - soil	Low potential for mobility in soil. May be harmful to plant growth, blooming and fruit formation.
----------------	---

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Disposal methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

Mineral Spirits (Regular)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

- Product/Packaging disposal recommendations : Remove waste in accordance with local and/or national regulations. Hazardous waste shall not be mixed together with other waste. Different types of hazardous waste shall not be mixed together if this may entail a risk of pollution or create problems for the further management of the waste. Hazardous waste shall be managed responsibly. All entities that store, transport or handle hazardous waste shall take the necessary measures to prevent risks of pollution or damage to people or animals.
- Additional information : Flammable vapors may accumulate in the container.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

- Transport document description : UN1268 Petroleum distillates, n.o.s., 3, III
- UN-No.(DOT) : UN1268
- Proper Shipping Name (DOT) : Petroleum distillates, n.o.s.
- Class (DOT) : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120
- Packing group (DOT) : III - Minor Danger
- Hazard labels (DOT) : 3 - Flammable liquid



- DOT Packaging Non Bulk (49 CFR 173.xxx) : 203
- DOT Packaging Bulk (49 CFR 173.xxx) : 242
- DOT Special Provisions (49 CFR 172.102) : 144 - If transported as a residue in an underground storage tank (UST), as defined in 40 CFR 280.12, that has been cleaned and purged or rendered inert according to the American Petroleum Institute (API) Standard 1604 (IBR, see 171.7 of this subchapter), then the tank and this material are not subject to any other requirements of this subchapter. However, sediments remaining in the tank that meet the definition for a hazardous material are subject to the applicable regulations of this subchapter.
B1 - If the material has a flash point at or above 38 C (100 F) and below 93 C (200 F), then the bulk packaging requirements of 173.241 of this subchapter are applicable. If the material has a flash point of less than 38 C (100 F), then the bulk packaging requirements of 173.242 of this subchapter are applicable.
IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672).
T4 - 2.65 178.274(d)(2) Normal..... 178.275(d)(3)
TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = $97 / 1 + a (tr - tf)$ Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling.
TP29 - A portable tank having a minimum test pressure of 1.5 bar (150.0 kPa) may be used provided the calculated test pressure is 1.5 bar or less based on the MAWP of the hazardous materials, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP.
- DOT Packaging Exceptions (49 CFR 173.xxx) : 150
- DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : 60 L
- DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 220 L
- DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.
- Emergency Response Guide (ERG) Number : 128
- Other information : No supplementary information available.

Transportation of Dangerous Goods

Transport by sea

- Transport document description (IMDG) : UN 1268 PETROLEUM DISTILLATES, N.O.S., 3, III

Mineral Spirits (Regular)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

UN-No. (IMDG)	: 1268
Proper Shipping Name (IMDG)	: PETROLEUM DISTILLATES, N.O.S.
Class (IMDG)	: 3 - Flammable liquids
Packing group (IMDG)	: III - substances presenting low danger
Limited quantities (IMDG)	: 5 L

Air transport

Transport document description (IATA)	: UN 1268 Petroleum distillates, n.o.s., 3, III
UN-No. (IATA)	: 1268
Proper Shipping Name (IATA)	: Petroleum distillates, n.o.s.
Class (IATA)	: 3 - Flammable Liquids
Packing group (IATA)	: III - Minor Danger

SECTION 15: Regulatory information

15.1. US Federal regulations

Mineral Spirits (Regular) (8052-41-3)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Pseudocumene (95-63-6)

Listed on the United States TSCA (Toxic Substances Control Act) inventory
Subject to reporting requirements of United States SARA Section 313

Stoddard Solvent (8052-41-3)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard Fire hazard Delayed (chronic) health hazard
-------------------------------------	---

15.2. International regulations

CANADA

No additional information available

EU-Regulations

No additional information available

National regulations

No additional information available

15.3. US State regulations

Mineral Spirits (Regular) (8052-41-3)

State or local regulations	U.S. - New Jersey - Right to Know Hazardous Substance List
----------------------------	--

Component	State or local regulations
Pseudocumene(95-63-6)	U.S. - New Jersey - Right to Know Hazardous Substance List
Stoddard Solvent (8052-41-3)	U.S. - New Jersey - Right to Know Hazardous Substance List

SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date : 05/02/2018

Mineral Spirits (Regular)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Full text of H-phrases:

H226	Flammable liquid and vapor
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H319	Causes serious eye irritation
H332	Harmful if inhaled
H335	May cause respiratory irritation
H336	May cause drowsiness or dizziness
H340	May cause genetic defects
H350	May cause cancer
H360	May damage fertility or the unborn child
H373	May cause damage to organs through prolonged or repeated exposure
H411	Toxic to aquatic life with long lasting effects

NFPA health hazard


: 1 - Materials that, under emergency conditions, can cause significant irritation.

NFPA fire hazard

: 2 - Materials that must be moderately heated or exposed to relatively high ambient temperatures before ignition can occur.

NFPA reactivity

: 0 - Material that in themselves are normally stable, even under fire conditions.



SDS US (GHS HazCom 2012)

The information above is believed to be accurate and represents the best information currently available to us. However, we make no warranty of merchantability or any other warranty, express or implied, with respect to such information, and we assume no liability resulting from its use. Users should make their own investigations to determine the suitability of the information for their particular purposes. Please be advised revisions to the Safety Data Sheet (SDS) may require a label update. In no event shall ECOLINK be liable for any claims, losses, or damages of any third party or for lost profits or any special, indirect, incidental, consequential or exemplary damages, howsoever arising, even if ECOLINK has been advised of the possibility of such damages. The vendor assumes no responsibility for injury or damages resulting from the inappropriate alteration or manipulation of this SDS and its contents from that originally submitted by ECOLINK.