

### SECTION 1: Identification

#### 1.1. Identification

Product form : Substance  
 Substance name : 130W - 500W White Oils  
 CAS-No. : 8042-47-5  
 Synonyms : paraffineolie 15 / paraffineolie 15 (sip med 15) pharm. / purity FG WO 35 / purity FG WO 90 / shell ondina 917 / SHELL ONDINA OLIE 917 / shell risella 917 / slab oil (obs.) / vaseline olie / white mineral oil (petroleum)

#### 1.2. Recommended use and restrictions on use

Use of the substance/mixture : Rubber: Softener  
 Recommended use : Food/feedstuff additives, Lubricants, Greases and Release Products

#### 1.3. Supplier

##### **ECOLINK**

2177 Flintstone Drive  
 Suite A  
 Tucker, GA 30084  
 770-621-8240 (t)  
[www.ecolink.com](http://www.ecolink.com)

#### 1.4. Emergency telephone number

Emergency number : INFOTRAC 800-424-9300

### SECTION 2: Hazard(s) identification

#### 2.1. Classification of the substance or mixture

##### GHS-US classification

Not classified

#### 2.2. GHS Label elements, including precautionary statements

##### GHS-US labeling

No labeling applicable

#### 2.3. Other hazards which do not result in classification

No additional information available

#### 2.4. Unknown acute toxicity (GHS US)

Not applicable

### SECTION 3: Composition/Information on ingredients

#### 3.1. Substances

Name	Product identifier	%	GHS-US classification
130W - 500W White Oils (Main constituent)	(CAS-No.) 8042-47-5	100	Not classified

Full text of hazard classes and H-statements : see section 16

#### 3.2. Mixtures

Not applicable

### SECTION 4: First-aid measures

#### 4.1. Description of first aid measures

First-aid measures general : Check the vital functions. Unconscious: maintain adequate airway and respiration. Respiratory arrest: artificial respiration or oxygen. Cardiac arrest: perform resuscitation. Victim conscious with labored breathing: half-seated. Victim in shock: on his back with legs slightly raised. Vomiting: prevent asphyxia/aspiration pneumonia. Prevent cooling by covering the victim (no warming up). Keep watching the victim. Give psychological aid. Keep the victim calm, avoid physical strain. Depending on the victim's condition: doctor/hospital.

First-aid measures after inhalation : Remove the victim into fresh air. Respiratory problems: consult a doctor/medical service.

First-aid measures after skin contact : Rinse with water. Soap may be used. Take victim to a doctor if irritation persists.

# 130W - 500W White Oils

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

First-aid measures after eye contact	: Rinse with water. Remove contact lenses, if present and easy to do. Continue rinsing. Take victim to an ophthalmologist if irritation persists.
First-aid measures after ingestion	: Rinse mouth with water. Immediately after ingestion: give lots of water to drink. Do not induce vomiting. Call Poison Control Center. Consult a doctor/medical service if you feel unwell. Ingestion of large quantities: immediately to hospital.

### 4.2. Most important symptoms and effects (acute and delayed)

Potential Adverse human health effects and symptoms	: May be fatal if swallowed and enters airways. Practically non-toxic in contact with skin (LD50 skin > 2000 mg/kg). Not irritant to skin. Practically non-toxic by inhalation (LC50 inh, rat > 5 mg/l/4h). Not irritant to eyes.
Symptoms/effects after inhalation	: Coughing.
Symptoms/effects after skin contact	: Not irritating.
Symptoms/effects after eye contact	: Not irritating.
Symptoms/effects after ingestion	: Risk of aspiration pneumonia. Coughing. Respiratory difficulties. Gastrointestinal complaints. Nausea. Vomiting. Diarrhoea.
Chronic symptoms	: No effects known.

### 4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

## SECTION 5: Fire-fighting measures

### 5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media	: Quick-acting ABC powder extinguisher. Quick-acting BC powder extinguisher. Quick-acting class B foam extinguisher. Quick-acting CO2 extinguisher. Class B foam (not alcohol-resistant).
Unsuitable extinguishing media	: Water (quick-acting extinguisher, reel); risk of puddle expansion. Water; risk of puddle expansion.

### 5.2. Specific hazards arising from the chemical

Fire hazard	: DIRECT FIRE HAZARD: Non-flammable. INDIRECT FIRE HAZARD: Temperature above flashpoint: higher fire/explosion hazard.
Reactivity	: Reacts with (strong) oxidizers.

### 5.3. Special protective equipment and precautions for fire-fighters

Precautionary measures fire	: Exposure to fire/heat: keep upwind. Exposure to fire/heat: have neighborhood close doors and windows.
Firefighting instructions	: Cool tanks/drums with water spray/remove them into safety. Take account of environmentally hazardous firefighting water. Use water moderately and if possible collect or contain it.
Protection during firefighting	: Heat/fire exposure: compressed air/oxygen apparatus.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

#### 6.1.1. For non-emergency personnel

Protective equipment	: Gloves. Protective clothing.
Emergency procedures	: Mark the danger area. No naked flames. Wash contaminated clothes.

#### 6.1.2. For emergency responders

Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
----------------------	---

### 6.2. Environmental precautions

Prevent soil and water pollution. Prevent spreading in sewers.

### 6.3. Methods and material for containment and cleaning up

For containment	: Contain released product, pump into suitable containers. Plug the leak, cut off the supply. Dam up the liquid spill.
Methods for cleaning up	: Take up liquid spill into a non combustible material e.g.: sand. Scoop absorbed substance into closing containers. Carefully collect the spill/leftovers. Clean contaminated surfaces with an excess of water. Take collected spill to manufacturer/competent authority. Wash clothing and equipment after handling.
Other information	: Dispose of materials or solid residues at an authorized site.

### 6.4. Reference to other sections

For further information refer to section 13.

# 130W - 500W White Oils

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

- Precautions for safe handling : Keep away from naked flames/heat. In finely divided state: use spark-/explosion-proof appliances. Finely divided: keep away from ignition sources/sparks. Carry operations in the open/under local exhaust/ventilation or with respiratory protection. Comply with the legal requirements. Remove contaminated clothing immediately. Clean contaminated clothing. Thoroughly clean/dry the installation before use. Do not discharge the waste into the drain.
- Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

#### 7.2. Conditions for safe storage, including any incompatibilities

- Storage conditions : Store locked up. Store in a well-ventilated place. Keep cool.
- Heat-ignition : KEEP SUBSTANCE AWAY FROM: heat sources.
- Information on mixed storage : KEEP SUBSTANCE AWAY FROM: oxidizing agents.
- Storage area : Store in a cool area. Keep out of direct sunlight. Ventilation at floor level. Fireproof storeroom. Provide for a tub to collect spills. Meet the legal requirements.
- Special rules on packaging : SPECIAL REQUIREMENTS: closing. correctly labelled. meet the legal requirements. Secure fragile packagings in solid containers.

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

##### 130W - 500W White Oils (8042-47-5)

ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	5 mg/m <sup>3</sup> (Inhalable fraction)
-------	--------------------------------	--

#### 8.2. Appropriate engineering controls

- Appropriate engineering controls : Ensure good ventilation of the work station.
- Environmental exposure controls : Avoid release to the environment.

#### 8.3. Individual protection measures/Personal protective equipment

##### Materials for protective clothing:

GIVE GOOD RESISTANCE: PVC. neoprene. nitrile rubber

##### Hand protection:

Gloves

##### Eye protection:

Eye protection not required in normal conditions

##### Skin and body protection:

Protective clothing

##### Respiratory protection:

Full face mask with filter type A at conc. in air > exposure limit

### SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

- Physical state : Liquid
- Appearance : Liquid.
- Color : Colorless
- Odor : Odorless
- Odor threshold : No data available
- pH : No data available
- Melting point : Not applicable
- Freezing point : No data available
- Boiling point : 218 - 800 °C (1013 hPa)
- Flash point : > 112 °C (Closed cup, 1013 hPa)

# 130W - 500W White Oils

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: Not applicable.
Vapor pressure	: < 0.1 hPa (20 °C)
Relative vapor density at 20 °C	: > 1
Relative density	: 0.81 - 0.89 (15 °C)
Specific gravity / density	: 810 - 894 kg/m <sup>3</sup> (15 °C)
Solubility	: Insoluble in water. Water: insoluble
Log Pow	: > 6 (Calculated)
Auto-ignition temperature	: 325 - 355 °C (1013 hPa)
Decomposition temperature	: No data available
Viscosity, kinematic	: > 20.5 cSt
Viscosity, dynamic	: No data available
Explosion limits	: 1 - 10 vol % LEL: 1 vol % UEL: 10 vol %
Explosive properties	: No data available
Oxidizing properties	: No data available

### 9.2. Other information

VOC content	: 0 %
Other properties	: Gas/vapour heavier than air at 20°C. Slightly volatile.

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Reacts with (strong) oxidizers.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

### 10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

### 10.5. Incompatible materials

No additional information available

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity : Not classified

130W - 500W White Oils (8042-47-5)	
LD50 oral rat	> 5000 mg/kg body weight (Equivalent or similar to OECD 401, Rat, Male/female, Experimental value)
LD50 dermal rabbit	> 2000 mg/kg body weight (Equivalent or similar to OECD 402, 24 h, Rabbit, Male/female, Experimental value)
LC50 inhalation rat (mg/l)	> 5 mg/l (Equivalent or similar to OECD 403, 4 h, Rat, Male/female, Experimental value)

Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
Specific target organ toxicity – single exposure	: Not classified

# 130W - 500W White Oils

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Specific target organ toxicity – repeated exposure	: Not classified
Aspiration hazard	: Not classified
Potential Adverse human health effects and symptoms	: May be fatal if swallowed and enters airways. Practically non-toxic in contact with skin (LD50 skin > 2000 mg/kg). Not irritant to skin. Practically non-toxic by inhalation (LC50 inh, rat > 5 mg/l/4h). Not irritant to eyes.
Symptoms/effects after inhalation	: Coughing.
Symptoms/effects after skin contact	: Not irritating.
Symptoms/effects after eye contact	: Not irritating.
Symptoms/effects after ingestion	: Risk of aspiration pneumonia. Coughing. Respiratory difficulties. Gastrointestinal complaints. Nausea. Vomiting. Diarrhoea.
Chronic symptoms	: No effects known.

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general	: The product is not considered harmful to aquatic organisms or to cause long-term adverse effects in the environment.
Ecology - air	: Not included in the list of fluorinated greenhouse gases (Regulation (EU) No 517/2014). Photooxidation in the air. Not classified as dangerous for the ozone layer (Regulation (EC) No 1005/2009).
Ecology - water	: Slightly harmful to crustacea. Slightly harmful to fishes. Groundwater pollutant. Slightly harmful to algae.

#### 130W - 500W White Oils (8042-47-5)

LC50 fish 1	> 100 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Oncorhynchus mykiss, Static system, Fresh water, Experimental value)
-------------	---

### 12.2. Persistence and degradability

#### 130W - 500W White Oils (8042-47-5)

Persistence and degradability	Not readily biodegradable in water.
-------------------------------	-------------------------------------

### 12.3. Bioaccumulative potential

#### 130W - 500W White Oils (8042-47-5)

Log Pow	> 6 (Calculated)
Bioaccumulative potential	High potential for bioaccumulation (Log Kow > 5).

### 12.4. Mobility in soil

#### 130W - 500W White Oils (8042-47-5)

Ecology - soil	Adsorbs into the soil.
----------------	------------------------

### 12.5. Other adverse effects

No additional information available

## SECTION 13: Disposal considerations

### 13.1. Disposal methods

Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Product/Packaging disposal recommendations	: Use appropriate containment to avoid environmental contamination. Remove waste in accordance with local and/or national regulations. Remove to an authorized plant for the destruction, neutralization and elimination of hazardous waste. Hazardous waste shall not be mixed together with other waste. Different types of hazardous waste shall not be mixed together if this may entail a risk of pollution or create problems for the further management of the waste. Hazardous waste shall be managed responsibly. All entities that store, transport or handle hazardous waste shall take the necessary measures to prevent risks of pollution or damage to people or animals.

# 130W - 500W White Oils

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 14: Transport information

#### Department of Transportation (DOT)

In accordance with DOT Not Regulated for Transport

#### Transportation of Dangerous Goods

#### Transport by sea

#### Air transport

### SECTION 15: Regulatory information

#### 15.1. US Federal regulations

##### 130W - 500W White Oils (8042-47-5)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

#### 15.2. International regulations

##### CANADA

No additional information available

##### EU-Regulations

No additional information available

##### National regulations


No additional information available

#### 15.3. US State regulations

No additional information available

### SECTION 16: Other information

Revision date	: 04/12/2018
NFPA health hazard	: 0 - Materials that, under emergency conditions, would offer no hazard beyond that of ordinary combustible materials.
NFPA fire hazard	: 1 - Materials that must be preheated before ignition can occur.
NFPA reactivity	: 0 - Material that in themselves are normally stable, even under fire conditions.



SDS US (GHS HazCom 2012)

*The information above is believed to be accurate and represents the best information currently available to us. However, we make no warranty of merchantability or any other warranty, express or implied, with respect to such information, and we assume no liability resulting from its use. Users should make their own investigations to determine the suitability of the information for their particular purposes. Please be advised revisions to the Safety Data Sheet (SDS) may require a label update. In no event shall ECOLINK be liable for any claims, losses, or damages of any third party or for lost profits or any special, indirect, incidental, consequential or exemplary damages, howsoever arising, even if ECOLINK has been advised of the possibility of such damages. The vendor assumes no responsibility for injury or damages resulting from the inappropriate alteration or manipulation of this SDS and its contents from that originally submitted by ECOLINK.*