

Page 1

Safety Data Sheet (SDS) OSHA Hazard Communication Standard 29 CFR 1910.1200. Prepared to GHS Rev03.

Reviewed on 2/23/2020

| ELECTRON (A) |) 365-1 | 12 x 16 oz net Aerosol | | |
|---|---|---|------------------------|------------------------|
| | | 12 X TO UZ TIEL AETUSUI | 6850-01-371-8048 | |
| Manufacturer/ Ecolink 2177 Flintstone Tucker, GA 300 www.ecolink.cc 800-886-8240 (| Supplier: 9 Dr., Ste. A 084 0m 0r 770-621-8 | | | email: info@ecolink.c |
| | | nber: Infotrac: 1-800-535-5 | 5053, 1-352-326-2510 | , |
| | | | | |
| ? Hazard(s) id | lentificatic | n | | |
| | | | | |
| <u> </u> | | | | |
| · Classification | of the subs | ance or mixture | | |
| · Classification | of the subs | tance or mixture | | |
| | of the subs | ance or mixture | | |
| | | ance or mixture | | |
| с С С С С С С С С С С С С С С С С С С С | 02 Flame | | | Acus burget if boosted |
| с С С С С С С С С С С С С С С С С С С С | 02 Flame | 9 Flammable aerosol. Pr | essurized container: N | Nay burst if heated. |
| с С С С С С С С С С С С С С С С С С С С | 02 Flame | | essurized container: N | Nay burst if heated. |
| GHSU Flam. Aerosol 2 | 02 Flame 2 H223-22 | 9 Flammable aerosol. Pr | essurized container: N | Nay burst if heated. |
| GHSU Flam. Aerosol 2 | 02 Flame | 9 Flammable aerosol. Pr | essurized container: N | Nay burst if heated. |
| Flam. Aerosol 2 | 02 Flame 2 H223-22 08 Health ha. | 9 Flammable aerosol. Pro | | |
| Flam. Aerosol 2 | 02 Flame 2 H223-22 08 Health ha. | 9 Flammable aerosol. Pr | | |
| Flam. Aerosol 2 | 02 Flame 2 H223-22 08 Health ha. | 9 Flammable aerosol. Pro | | |
| Flam. Aerosol 2 Flam. Aerosol 2 GHSC Asp. Tox. 1 | 02 Flame 2 H223-22 08 Health ha H304 | 9 Flammable aerosol. Pro | | |
| Flam. Aerosol 2 | 02 Flame 2 H223-22 08 Health ha H304 | 9 Flammable aerosol. Pro | | |
| Flam. Aerosol 2 Flam. Aerosol 2 GHSC Asp. Tox. 1 | 02 Flame 2 H223-22 08 Health ha H304 | 9 Flammable aerosol. Pro | | |
| Flam. Aerosol 2 Flam. Aerosol 2 GHSC Asp. Tox. 1 | 02 Flame 2 H223-22 08 Health ha H304 | 9 Flammable aerosol. Pro | | |
| Flam. Aerosol 2 Flam. Aerosol 2 GHSC Asp. Tox. 1 GHSC Skin Irrit. 2 | 02 Flame 2 H223-22 08 Health ha H304 07 H315 | 9 Flammable aerosol. Pro zard May be fatal if swallowe Causes skin irritation. | ed and enters airways | |
| Flam. Aerosol 2 Flam. Aerosol 2 GHSC Asp. Tox. 1 GHSC | 02 Flame 2 H223-22 08 Health ha H304 07 | 9 Flammable aerosol. Pro zard May be fatal if swallowe | ed and enters airways | |
| Flam. Aerosol 2 Flam. Aerosol 2 GHSC Asp. Tox. 1 GHSC Skin Irrit. 2 Skin Sens. 1 | 02 Flame 2 H223-22 08 Health ha H304 07 H315 H317 | 9 Flammable aerosol. Pro zard May be fatal if swallowe Causes skin irritation. | ed and enters airways | |
| Flam. Aerosol 2 Flam. Aerosol 2 GHSC Asp. Tox. 1 GHSC Skin Irrit. 2 | 02 Flame 2 H223-22 08 Health ha H304 07 H315 H317 | 9 Flammable aerosol. Pro zard May be fatal if swallowe Causes skin irritation. | ed and enters airways | |
| Flam. Aerosol 2 Flam. Aerosol 2 GHSC Asp. Tox. 1 GHSC Skin Irrit. 2 Skin Sens. 1 | 02 Flame 2 H223-22 08 Health ha H304 07 H315 H317 | 9 Flammable aerosol. Pro zard May be fatal if swallowe Causes skin irritation. | ed and enters airways | |
| Flam. Aerosol 2 Flam. Aerosol 2 GHSC Asp. Tox. 1 GHSC Skin Irrit. 2 Skin Sens. 1 Label element GHS label elem | 02 Flame 2 H223-22 08 Health ha H304 07 H315 H317 s ments | 9 Flammable aerosol. Pro zard May be fatal if swallowe Causes skin irritation. | ed and enters airways | |



ia Ecolink.

Safety Data Sheet (SDS)

OSHA Hazard Communication Standard 29 CFR 1910.1200. Prepared to GHS Rev03.

Reviewed on 2/23/2020



· Description: Mixture of the substances listed below with nonhazardous additions.

(Contd. on page 3)



IZ ECOLINK.

Safety Data Sheet (SDS)

OSHA Hazard Communication Standard 29 CFR 1910.1200. Prepared to GHS Rev03.

Reviewed on 2/23/2020

Trade name: ELECTRON Aerosol

| · Dangerous components: | |
|---|--------|
| 64742-48-9 Naphtha (petroleum), hydrotreated heavy | 60-90% |
| Asp. Tox. 1, H304; H227 | |
| 68647-72-3 Citrus Terpene | 25-50% |
| Flam. Liq. 3, H226; Asp. Tox. 1, H304; Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Skin Irrit. 2, H315; Skin Sens. 1, H317 | |
| 124-38-9 Carbon dioxide | 2-12% |
| Press. Gas, H280 | |

4 First-aid measures

· Description of first aid measures

- · After inhalation:
- Supply fresh air and to be sure call for a doctor.

In case of unconsciousness, place patient securely in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water.
- After swallowing: Give large amounts of water. If symptoms persist consult doctor.
- · Information for doctor:
- *Most important symptoms and effects, both acute and delayed* No further relevant information available.
- Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

- Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
- Environmental precautions: Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers, surface or ground water.
- *Methods and material for containment and cleaning up:* Dispose contaminated material as waste according to section 13. Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

• Reference to other sections See Section 7 for information on safe handling.

(Contd. on page 4)



ia. Ecolink.

Safety Data Sheet (SDS)

OSHA Hazard Communication Standard 29 CFR 1910.1200. Prepared to GHS Rev03.

Reviewed on 2/23/2020

Trade name: ELECTRON Aerosol

See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

7 Handling and storage

- · Handling:
- · Precautions for safe handling Ensure good ventilation/exhaustion at the workplace. Open and handle receptacle with care. Information about protection against explosions and fires: Do not spray on a naked flame or any incandescent material. Keep ignition sources away - Do not smoke. Protect from heat. Protect against electrostatic charges. Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C, i.e. electric lights. Do not pierce or burn, even after use. · Conditions for safe storage, including any incompatibilities · Storage: · Requirements to be met by storerooms and receptacles: Store in a cool location. Observe official regulations on storing packagings with pressurized containers. · Information about storage in one common storage facility: Not required. · Further information about storage conditions: Keep receptacle tightly sealed. Do not gas tight seal receptacle.

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

· Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

· Additional information about design of technical systems: No further data; see section 7.

- · Control parameters
- Components with limit values that require monitoring at the workplace: 124-38-9 Carbon dioxide
- PEL Long-term value: 9,000 mg/m3, 5,000 ppm
- REL Short-term value: 54,000 mg/m3, 30,000 ppm Long-term value: 9,000 mg/m3, 5,000 ppm
- TLV Short-term value: 54,000 mg/m3, 30,000 ppm Long-term value: 9,000 mg/m3, 5,000 ppm
- Additional information: The lists that were valid during the creation were used as basis.

Exposure controls

- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

(Contd. on page 5)

USA



OSHA Hazard Communication Standard 29 CFR 1910.1200. Prepared to GHS Rev03.

Reviewed on 2/23/2020

Trade name: ELECTRON Aerosol

(Contd. of page 4)

Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Avoid contact with the skin. Avoid contact with the eyes and skin.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure, use respiratory protective device that is independent of circulating air. • **Protection of hands:**



ECO

INK.

Protective gloves

The glove material has to be impermeable and resistant to the product. Due to missing tests no recommendation to the glove material can be given for the product. Select glove material based on penetration times, rates of diffusion and degradation.

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break-through time has to be determined and observed by the manufacturer of the protective gloves.

· Eye protection: Tightly sealed goggles or safety glasses with side shields

| Information on basic physical and General Information | chennoai properties | |
|---|---|--|
| Appearance: Form: Color: Odor: Odor threshold: | Liquid Colorless Mild citrus terpene Not determined. | |
| pH-value: | Not determined. | |
| Change in condition Melting point/Melting range: Boiling point/Boiling range: | Not determined. 160 °C (320 °F) | |
| Flash point: | 43 °C (109 °F) | |
| Flammability (solid, gaseous): | Not applicable. | |
| Ignition temperature: | 240 °C (464 °F) | |
| Decomposition temperature: | Not determined. | |



IE ECOLINK.

Safety Data Sheet (SDS)

OSHA Hazard Communication Standard 29 CFR 1910.1200. Prepared to GHS Rev03.

Reviewed on 2/23/2020

Trade name: ELECTRON Aerosol

| Auto igniting: | Product is not self-igniting. |
|---|--|
| Danger of explosion: | Product is not explosive. However, formation of explosive air/ vapor mixtures are possible. |
| Explosion limits: Lower: Upper: | 0.6 Vol % 7.0 Vol % |
| Vapor pressure @ 20 °C (68 °F): | 1 hPa (1 mm Hg) |
| Density @ 20 °C (68 °F): Relative density @ 20 °C (68 °F) Vapor density Evaporation rate | 0.784 g/cm³ (6.542 lbs/gal) 6.54 lbs/gal >1.0 (air = 1). Not applicable. |
| Solubility in / Miscibility with Water: | Not miscible or difficult to mix. |
| Partition coefficient (n-octanol/wate | er): Not determined. |
| Viscosity: Dynamic: Kinematic: | Not determined. Not determined. |
| Solvent content: Organic solvents: Other information | 95 % No further relevant information available. |

10 Stability and reactivity

· Reactivity No further relevant information available.

- · Chemical stability
- **Thermal decomposition** / **conditions to be avoided:** No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: Strong oxidizing agents.
- · Hazardous decomposition products: Oxides of carbon.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:

· LD/LC50 values that are relevant for classification:

- 64742-48-9 Naphtha (petroleum), hydrotreated heavy
- Oral LD50 >5,000 mg/kg (rat)
- Dermal LD50 >3,000 mg/kg (rabbit)

(Contd. on page 7) USA



OSHA Hazard Communication Standard 29 CFR 1910.1200. Prepared to GHS

Rev03.

Reviewed on 2/23/2020

Trade name: ELECTRON Aerosol

· Primary irritant effect:

ECOLINK.

- on the skin: Irritant to skin and mucous membranes.
- · on the eye: No irritating effect.
- · Sensitization: Sensitization possible through skin contact.
- Additional toxicological information: The product shows the following dangers according to internally approved calculation methods for preparations: Irritant
- · Carcinogenic categories
- *IARC (International Agency for Research on Cancer)* None of the ingredients is listed.
- NTP (National Toxicology Program)

None of the ingredients is listed.

12 Ecological information

- · Toxicity
- Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- Ecotoxical effects:
- · Remark: Very toxic for fish
- · Additional ecological information:
- · General notes:

Water hazard class 3 (Self-assessment): extremely hazardous for water

Do not allow product to reach ground water, water course or sewage system, even in small quantities. Danger to drinking water if even extremely small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Very toxic for aquatic organisms

· Results of PBT and vPvB assessment

- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

· Waste treatment methods

· Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

(Contd. on page 8)

USA



Page 8

Safety Data Sheet (SDS) OSHA Hazard Communication Standard 29 CFR 1910.1200. Prepared to GHS Rev03.

Reviewed on 2/23/2020

Trade name: ELECTRON Aerosol

· Uncleaned packagings:

· Recommendation: Disposal must be made according to official regulations.

| UN-Number DOT, ADR, IMDG, IATA | UN1950 |
|---|---|
| UN proper shipping name DOT ADR IMDG IATA | Aerosols, flammable UN1950 Aerosols, ENVIRONMENTALLY HAZARDOUS AEROSOLS (Citrus Terpene), MARINE POLLUTANT AEROSOLS, flammable |
| Transport hazard class(es) | |
| рот | |
| Class Label | 2.1 2.1 |
| ADR | |
| Class Label | 2 5F Gases 2.1 |
| IMDG | |
| Class Label | 2.1 2.1 |
| | |
| Class Label | 2.1 2.1 |





OSHA Hazard Communication Standard 29 CFR 1910.1200. Prepared to GHS Rev03.

Reviewed on 2/23/2020

Trade name: ELECTRON Aerosol

| Packing group DOT, ADR, IMDG, IATA | Non-Regulated Material | | |
|--|--|--|--|
| Environmental hazards: | Product contains environmentally hazardous substances: Citrus Terpene | | |
| Marine pollutant: | Yes Symbol (fish and tree) Symbol (fish and tree) | | |
| Special marking (ADR): | | | |
| Special precautions tor user | Warning: Gases | | |
| Danger code (Kemler): EMS Number: | - F-D,S-U | | |
| <i>Transport in bulk according to Annex</i> <i>MARPOL73/78 and the IBC Code</i> | <i>Il ot</i> Not applicable. | | |
| Transport/Additional intormation: | | | |
| DOT | | | |
| Remarks: | ORM-D Limited QTY Item | | |
| UN "Model Regulation": | UN 1950, Aerosols , ENVIRONMENTALLY HAZARDOUS, 2.1 | | |

15 Regulatory intormation

- \cdot Safety, health and environmental regulations/legislation specific tor the substance or mixture \cdot Sara
- Section 355 (extremely hazardous substances): None of the ingredients is listed.
- Section 313 (Specific toxic chemical listings): None of the ingredients is listed.
- **TSCA (Toxic Substances Control Act):** All ingredients are listed.
- · Proposition 65
- Chemicals known to cause cancer: None of the ingredients is listed.
- Chemicals known to cause reproductive toxicity tor females: None of the ingredients is listed.
- Chemicals known to cause reproductive toxicity tor males: None of the ingredients is listed.
- Chemicals known to cause developmental toxicity: None of the ingredients is listed.

(Contd. on page 10) USA



ie Ecolink.

Safety Data Sheet (SDS)

OSHA Hazard Communication Standard 29 CFR 1910.1200. Prepared to GHS Rev03.

Reviewed on 2/23/2020

Trade name: ELECTRON Aerosol

(Contd. of page 9)

- · Carcinogenic categories
- EPA (Environmental Protection Agency) None of the ingredients is listed.
- TLV (Threshold Limit Value established by ACGIH) None of the ingredients is listed.
- NIOSH-Ca (National Institute tor Occupational Satety and Health) None of the ingredients is listed.
- · OSHA-Ca (Occupational Satety & Health Administration) Corrosive to eyes
- · GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS). • Hazard pictograms



· Signal word Danger

· Hazard-determining components of labeling:

Naphtha (petroleum), hydrotreated heavy

Citrus Terpene

Hazard statements

- H223+H229 Flammable aerosol. Pressurized container: May burst if heated.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H304 May be fatal if swallowed and enters airways.

· Precautionary statements

Precautionary statements

- P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.
- P251 Pressurized container: Do not pierce or burn, even after use. Do not spray on an open flame or other ignition sources.
- P301+P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. P405 Store locked up.
- P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
- *P501 Dispose of contents/container in accordance with local/national/international regulations.*

National regulations:

The product is subject to be labeled according with the prevailing version of the regulations on hazardous substances.

· State Right to Know

64742-48-9 Naphtha (petroleum), hydrotreated heavy Asp. Tox. 1, H304; H227 60-90%

(Contd. on page 11) USA





OSHA Hazard Communication Standard 29 CFR 1910.1200. Prepared to GHS Rev03.

Reviewed on 2/23/2020

Trade name: ELECTRON Aerosol

68647-72-3 Citrus Terpene

25-50%

Flam. Liq. 3, H226; Asp. Tox. 1, H304; Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Skin Irrit. 2, H315; Skin Sens. 1, H317 124-38-9 Carbon dioxide

2-12%

Press. Gas, H280

None of the ingredients is listed.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Date of preparation / last revision 8/31/2015

 Abbreviations and acronyms:
ADR: Accord europeen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
DOT: US Department of Transportation
IATA: International Air Transport Association
ACGIH: American Conference of Governmental Industrial Hygienists
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
NFPA: National Fire Protection Association (USA)
HMIS: Hazardous Materials Identification System (USA)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent

SDS Created by MSDS Authoring Services (www.MSDSAuthoring.com)

USA