

# ECOLINK 1171



## Low VOC Degreasing Solvent Product Data Sheet

PO Box 9  
Tucker, GA 30084  
800-886-8240 • 770-621-8240  
[www.ecolink.com](http://www.ecolink.com)  
email: [info@ecolink.com](mailto:info@ecolink.com)

### Description

ECOLINK 1171 is a low VOC (25 gm/l) solvent degreaser formulated without Class II ozone depleting substances. ECOLINK 1171 will evaporate at about the same rate as isopropyl alcohol (IPA) without leaving a residue. ECOLINK 1171 is safe for use on ferrous and non-ferrous metals.

ECOLINK 1171 is strong enough to remove grease, fuel oil, carbon and organic resins yet safe on most painted surfaces. After hand wipe cleaning with ECOLINK 1171, surfaces are ready for painting, bonding or other critical applications.

### Benefits

- Excellent solvency for a wide range of soils
- Evaporates quickly – similar to IPA
- Leaves no residue
- Low VOC – meets stringent air quality standards
- Controlled vapor pressure

### Applications

Use undiluted. Spray or wipe ECOLINK 1171 on surface to be cleaned, oil dirt and carbon will flow off surface. Reapply if necessary.

To speed the drying process, wipe the surface with a dry cloth or use compressed air.

Ecolink 1171 may also be used for flushing of paint guns.

### Safety and Handling Precautions

ECOLINK 1171 is a flammable material that should never be used around open flames, (welding torches, for example). Always use with adequate ventilation. Rubber gloves are recommended. Place rags in a metal sealable container after use to avoid possible spontaneous combustion. Keep container closed. Avoid excessive contact with fumes or liquid. Consult MSDS.

### Key Physical Characteristics

<u>Property</u>	<u>Value</u>
Appearance	Clear colorless liquid
Odor	Sweet naphthalenic
Flash Point, Tag Closed Cup	32°F
Evaporation Rate (nBuAc=1)	~1.4
Specific Gravity	1.254
Vapor Pressure (mm Hg)	Approx. 44 @ 20°C
VOC Content	25 grams/liter
Distillation Range	: 132 - 280° F
Shelf Life	2 Years Minimum

### Packaging

<u>Product Name</u>	<u>Part No.</u>	<u>Packaging</u>
ECOLINK 1171	1171 -55	55 Gal Drum
ECOLINK 1171	1171 -5	5 Gal Pail
ECOLINK 1171	1171 -1	4x1 Gal Case