

Material Safety Data Sheet



Parts Kleen Plus High Purity Parts Washing Solvent

Rev. 06/11/2012

2177A Flintstone Drive
TUCKER, GA 30084
www.ecolink.com
email: info@ecolink.com
800/886-8240 or
770/621-8240 (9-5 EST)

FOR CHEMICAL EMERGENCY
Call INFOTRAC
800/535-5053 (24 HOURS)

Section I: Product Identification

Product name: Parts Kleen Plus
Synonym: Solvent Degreaser
Molecular Formula: Proprietary Blend

Section II: Chemical or Hazardous Components

Chemical Name	Severely Hydrotreated Light Distillate
CAS No.	64742-47-8
% By Weight	50-70
Exposure	(*) MREL – 100 ppm TWA
ACGIH-TLV	N/E

Chemical Name	Terpene Hydrocarbons
CAS No.	(Mixture) Does not apply
% By Weight	30-50%
Exposure	ACGIH-TLV – N/E OSHA-PEL – N/E

This product contains highly refined Terpene Hydrocarbons, which are not considered hazardous by EPA/RCRA.

RCRA REGULATED: No
CERCLA (superfund): N/A
ALL MATERIALS IN PRODUCT ARE TSCA LISTED.
DOT regulated: No
DOT haz. Class: N/A
DOT shipping name: N/A
DOT number: N/A
(Questions concerning DOT information refer to DOT manual CFR 49, chapter 1, 10/96 edition)

Section III: Physical Data

Appearance & Odor:	Colorless liquid with mild terpene odor.
Boiling Point:	348° F. @ 760 mm Hg
Evaporation Rate:	<1.0 (nBuAc = 1)
Solubility In Water:	Non-miscible
Specific Gravity:	0.821
VOC Content	821 grams/liter
Vapor Density (AIR=1):	Approx. 5.0
Vapor Pressure:	.52 mmHg @ 68°F
Percent Volatile:	100%

Section IV: Fire and Explosion Hazard Data

Flash Point (Method):
Bulk Liquid (TCC) 142° F

Flammable Limits:
LEL 0.7%
UEL 7.0%

Extinguishing Media:
Regular foam, water fog, carbon dioxide, dry chemical, class B.

Special Fire Fighting Procedures:
Keep fire exposed containers cool with water. Fire fighters should wear self-contained breathing apparatus with a full face piece operated in the positive pressure demand mode with appropriate gear and chemical resistant personal protective equipment.

Unusual Fire & Explosion Hazards:
Vapors are heavier than air and may travel along the ground or be moved by ventilation and ignited by heat, pilot lights, other flames and ignition sources at locations distant from material handling point. Never use welding or cutting torch on or near drum (even empty) because product can ignite explosively.

Section V: Reactivity Data

Stability: Stable

Conditions to Avoid:
Sources of ignition such as sparks, hot spots, welding, flames and cigarettes. Ignition/flash may result if concentration of product is in the flammable range. (See section IV for LEL and UEL values.)

Incompatibility (Materials to Avoid):
If mixed with strong oxidizing agents and/or acids there is the possibility of a dangerous chemical reaction.

Hazardous Decomposition:
May form carbon dioxide and carbon monoxide.

Hazardous Polymerization:
Will not occur.

Section VI: Health Hazard Data

Primary Routes of Exposure:
Oral, inhalation, & skin

Ingestion:
Swallowing large amounts may be harmful by causing gastrointestinal irritation.

Inhalation:
Breathing large amounts may be harmful by causing nose, throat, and respiratory tract irritation.

Eyes:

Irritant. Liquid contact will irritate eyes and may cause stinging, tearing, and redness.

Skin or Contact:

May cause mild irritation of redness and burning.

First Aid:

Ingestion: Seek medical attention immediately. If individual is drowsy or unconscious, do not give anything by mouth; place individual on left side with head down. Contact medical facility or poison control center for advice on whether to induce vomiting.

Inhalation: Remove to fresh air. If breathing is difficult, give oxygen. Keep person warm and quiet. Seek medical attention.

Eyes: Irrigate immediately with water for at least 15 minutes. Get medical attention if irritation persists.

Skin: Wash with soap and water. Thoroughly clean contaminated clothes and shoes before reuse. If symptoms persist, seek medical attention.

Carcinogen: NTP – Not Listed
IARC Monographs – None
OSHA REGS – Not Regulated

Section VII: Precautions for Safe Handling

HMIS Information:

Health – 1 / Reactivity – 0
Flammability – 2 Personal Protection – B

HMIS Definition:

0 – Minimal 1 – Slight 2 – Moderate 3 – Serious 4 – Extreme

“/” in the Health Category denotes material does not target any major organs.

“*” in the Health Category denotes material may target certain organs.

Eye Protection

Safety glasses and splash protection required.

Protective Gloves:

Nitrile gloves are recommended for extended exposure or immersion of hands. Butyl rubber gloves may be used for incidental contact.

Respiratory Protection:

Not required under conditions of normal use. If vapor mist is present, use NIOSH certified organic vapor mask.

Ventilation: Local exhaust hood or fan may be used.

Other Protective Clothing: None required under normal use.

Work Practices: Store rags used with this material in an airtight, metal container to prevent spontaneous combustion. Treat this chemical with respect and follow all MSDS instructions.

Section VIII: Control Measures

Small Spill: Absorb liquid on vermiculite, floor absorbent, or other absorbent material and transfer to hood.

Large Spill: Eliminate all ignition sources, (flares, flames including pilot lights, electrical sparks). Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed. Stop spill at source. Prevent from entering drains, sewers, streams, etc. If runoff occurs, notify authorities as required. Pump or vacuum transfer spilled product to clean containers for recovery. Transfer contaminated absorbent soil and other materials to containers for disposal.

Waste Disposal Method: EXP 1010-1 is not considered a RCRA regulated substance. Soils removed during cleaning may affect the hazard classification of your waste stream. If your waste stream remains non-hazardous (you need to check), the waste may be disposed of like used oil (in most states). Please call us if you need additional disposal information.

Precautions To Be Taken In Handling & Storing: Since empty containers contain product residues, all hazard precautions given in the material safety data sheet must be observed. All metal pails or drums should be grounded and/or bonded when material is transferred. Any use of this product in elevated temperature processes should be thoroughly evaluated to establish and maintain safe operating conditions. Sudden release of hot organic chemical vapors or mists from process equipment operating at elevated temperatures may result in ignition.

Other Precautions: Keep this and all chemicals out of the reach of children.

Section IX: Part Number & Packaging

Product Name	Part Number	Packaging
Parts Kleen Plus	0118-55	55 gallon drum
Parts Kleen Plus	0118-5	5 gallon pail

DISCLAIMER: Ecolink, Inc. believes the information contained herein is accurate. However, Ecolink makes no warranty, expressed or implied, regarding the accuracy of this data or the results to be obtained by the use thereof. Ecolink, Inc. assumes no responsibility for injury from the use of the product described herein.

END OF MSDS