

# Material Safety Data Sheet

## ELECTRON-22

### Environmentally Preferred Dielectric Solvent

Rev. 06/06/2007

2177A Flintstone Drive  
TUCKER, GA 30084  
[www.ecolink.com](http://www.ecolink.com)  
email: [info@ecolink.com](mailto:info@ecolink.com)  
800/886-8240 or  
770/621-8240 (9–5 EST)

**FOR CHEMICAL EMERGENCY**  
Call INFOTRAC  
800/535-5053 (24 HOURS)

#### Section I: Product Identification

Product name: ELECTRON-22  
Synonym: Proprietary Blend  
Molecular Formula: Proprietary Blend

#### The “Plain English” Section

Material Safety Data Sheets can be confusing. Federal law requires us to print a great deal of technical information, which probably won't help the non-scientist. ECOLINK includes this “PLAIN ENGLISH” section, written to address the questions and concerns of the average person. If you have additional health, safety or product questions, don't hesitate to call us at 800/886-8240.

**Health Hazards:** ELECTRON-22 is an industrial chemical. We call it “environmentally preferred” because it is intended to replace products that are more hazardous, (1,1,1 trichloroethane, mineral spirits, MEK, etc.). This does not mean that ELECTRON-22 is completely harmless. It is strong enough to remove tough industrial soils, so it can irritate your skin. We suggest you wear gloves, and avoid extended exposure to unprotected skin. Don't get it in your eyes, or breath large amounts of the vapor, (it will dry out your nasal passages). Used on a rag or from a spray bottle, the product won't produce fumes in any great quantity, (don't spray ELECTRON-22 under high pressure without adequate ventilation). For more exposure and first aid information, refer to MSDS Sections II, VI.

**Flashpoint:** ELECTRON-22's flashpoint is 147° F. This represents the temperature that the liquid must reach before it emits fumes that will ignite. This is pretty hot, so combustion in ordinary use isn't a big concern. If ELECTRON-22 is used on rags, the rags can ignite if exposed to an open flame because the solvent is “wicked” onto the cloth. Be sure to dispose of rags in an airtight container specifically designed to prevent spontaneous combustion. Don't use ELECTRON-22 or any other combustible solvent around welding or any other hot work area.

**Disposal:** Straight from the drum, ELECTRON-22 is **not** considered a hazardous waste product. Once it is contaminated with whatever you are cleaning, the resulting mixture may fall under a hazardous classification, depending on whether or not the material you are cleaning is hazardous. If you aren't sure how to dispose of used ELECTRON-22, give us a call and we will help you make the right decisions.

#### Section II: Chemical or Hazardous Components

Chemical Name	Citrus Terpene
CAS No.	68647-72-3
Approx. wt.%	>10%
Exposure	(*) MREL – 100 ppm

Chemical Name	Severely Hydrotreated Light Distillates
CAS No.	64742-47-8
Approx. wt. %	>75%
Exposure	(*) MREL – 100 ppm

(\*) Manufacturer's recommended exposure limits.

#### ALL MATERIALS IN PRODUCT ARE TSCA LISTED

RCRA REGULATED:	No
CERCLA (superfund):	N/A
DOT Regulated:	No
DOT Haz. Class:	N/A
DOT Shipping Name:	N/A
DOT Number:	N/A

(Questions concerning DOT information refer to DOT manual CFR 49, chapter 1, 10/96 editions)

#### Section III: Physical Data

Appearance & Odor:	Colorless liquid with mild citrus Terpene odor
Boiling Point:	349° F. @ 760 mm Hg
Evaporation Rate:	<1.0
Percent Volatile:	100%
Solubility In Water:	Negligible
Specific Gravity:	0.8112
VOC Content	810 gm/l
	122 gm/l less exempt compounds
Vapor Density (AIR=1):	>1
Vapor Pressure:	0.30 mm Hg @ 68°F

## Section IV: Fire and Explosion Hazard Data

Flash Point (Method):  
Bulk Liquid (TCC) 147° F

Flammable Limits:  
LEL 0.7%  
UEL 7.0%

Extinguishing Media:  
Regular foam, water fog, carbon dioxide, dry chemical, class B.

Special Fire Fighting Procedures:  
Keep fire exposed containers cool with water. Fire fighters should wear self-contained breathing apparatus with a full-face piece operated in the positive pressure demand mode with appropriate gear and chemical resistant personal protective equipment.

Unusual Fire & Explosion Hazards:  
Vapors are heavier than air and may travel along the ground or be moved by ventilation and ignited by heat, pilot lights, other flames and ignition sources at locations distant from material handling point. Never use welding or cutting torch on or near drum (even empty) because product can ignite explosively.

## Section V: Reactivity Data

Stability: Stable

Conditions to Avoid:  
Sources of ignition such as sparks, hot spots, welding, flames and cigarettes. Ignition/flash may result if concentration of product is in the flammable range. (See section IV for LEL and UEL values.)

Incompatibility (Materials to Avoid):  
Strong oxidizing agents and/or strong acids.

Hazardous Decomposition:  
May form carbon dioxide and carbon monoxide.

Hazardous Polymerization:  
Will not occur.

## Section VI: Health Hazard Data

Primary Routes of Exposure:  
Oral, inhalation, & skin

Ingestion:  
Swallowing large amounts may be harmful by causing gastrointestinal irritation.

Inhalation:  
Breathing large amounts may be harmful by causing nose, throat, and respiratory tract irritation.

Eyes:  
Irritant. Liquid contact will irritate eyes and may cause stinging, tearing, and redness.

Skin or Contact:  
May cause mild irritation of redness and burning.

## First Aid:

Ingestion: Seek medical attention immediately. If individual is drowsy or unconscious, do not give anything by mouth; place individual on left side with head down. Contact medical facility or Poison Control center for advice on whether to induce vomiting.

Inhalation: Remove to fresh air. If breathing is difficult, give oxygen. Keep person warm and quiet. Seek medical attention.

Eyes: Irrigate immediately with water for at least 15 minutes. Get medical attention if irritation persists.

Skin: Wash with soap and water. Thoroughly clean contaminated clothes and shoes before re-use. If symptoms persist, seek medical attention.

## Toxicity Data:

Acute Toxicity: Oral Toxicity (mice) – LD<sub>50</sub> 5.6–6.6 g/kg

Skin Toxicity: Absorption (rabbits) – LD<sub>50</sub> >5000 mg/kg

Carcinogen: NTP – Not Listed  
IARC Monographs – None  
OSHA REGS – Not Regulated

## Section VII: Precautions for Safe Handling

HMIS Information:  
Health – 1 / Reactivity – 0  
Flammability – 2 Personal Protection – B

HMIS Definition:  
0 – Minimal, 1 – Slight, 2 – Moderate, 3 – Serious, 4 – Extreme  
“/” in the Health Category denotes material does not target any major organs.  
“\*” In the Health Category denotes material may target certain organs.

Eye Protection  
Safety glasses and splash protection required.

Protective Gloves:  
Nitrile gloves.

Respiratory Protection:  
Not required under conditions of normal use. If vapor mist is present, use NIOSH certified organic vapor mask.

Ventilation: Local exhaust/hood or fan may be used.

Other Protective Clothing: None required under normal use.

Work Practices: Store rags used with this material in an airtight, metal container to prevent spontaneous combustion. Treat this chemical with respect and follow all MSDS instructions.

## Section VIII: Control Measures

Small Spill: Absorb liquid on vermiculite, floor absorbent, or other absorbent material and transfer to hood.

Large Spill: Eliminate all ignition sources, (flares, flames including pilot lights, electrical sparks). Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed. Stop spill at source.

Prevent from entering drains, sewers, streams, etc. If runoff occurs, notify authorities as required. Pump or vacuum transfer spilled product to clean containers for recovery. Transfer contaminated absorbent soil and other materials to containers for disposal.

Waste Disposal Method: ELECTRON-22 is to be disposed of according to local, state, and federal regulations. Please call us if you need additional disposal information.

Precautions To Be Taken In Handling & Storing: Since empty containers contain product residues, all hazard precautions given in the material safety data sheet must be observed. All metal pails or drums should be grounded and/or bonded when material is transferred. Any use of this product in elevated temperature processes should be thoroughly evaluated to establish and maintain safe operating conditions. Sudden release of hot organic chemical vapors or mists from process equipment operating at elevated temperatures may result in ignition.

Other Precautions: Keep this and all chemicals out of the reach of children.

## Section IX: Part Number & Packaging

<u>Product Name</u>	<u>Part No.</u>	<u>Packaging</u>	<u>National Stock No.</u>
ELECTRON -22	049-1	12 x 22 oz Pump Spray	6850-01-371-8049

### Other Packaging Sizes for ELECTRON

ELECTRON	0296-55	55 Gal Drum	6850-01-375-5555
ELECTRON	0296-5	6 Gal Pail	6850-01-375-5553
ELECTRON	0296-1	4 x 1 Gal BX	6850-01-375-5554
ELECTRON	096-12	12 Qt. BX	
ELECTRON	0164-1	12 x 1 Pint BX	
ELECTRON	365-1	12 x 16 oz net Aerosol	6850-01-371-8048

DISCLAIMER: Ecolink, Inc. believes the information contained herein is accurate. However, Ecolink makes no warranty, expressed or implied, regarding the accuracy of this data or the results to be obtained by the use thereof. Ecolink, Inc. assumes no responsibility for injury from the use of the product described herein.

END OF MSDS