

Contact and Precision Parts Cleaner Product Data Sheet

Description

This product is a non-flammable, ozone-safe, rapid drying, EPA SNAP approved, alternative safety solvent furnished in bulk or a convenient aerosol can. It contains no CFC's or petroleum distillates and has a 36,200 volt dielectric strength (ASTM D-877).

It has a powerful flushing action that penetrates and removes grease, grime, dirt, tar, wax and other contaminants from electrical equipment and motors, while energized.

Benefits

- Fast drying
- Non-flammable
- Non-conductive
- Powerful cleaning action
- Leaves absolutely no residue

Applications

FOR USE BY:

Boat Yards	Machine Shops
Industrial Operations	School Bus Yards
Construction Companies	Oil Field Services
Engine & Motor Rebuilders	Equipment Manufacturers
Air Conditioning Maintenance	

FOR USE ON:

Gears	Relays
Windings	Motors
Generators	Starters
Engine Parts	Bearings
Printing Equipment	Gas, Water & Electric Meters
Production Machinery	Assemblies of Electrical Equipment

Key Physical Characteristics

<u>Property</u>	<u>Typical Value</u>
Boiling Point	188° F
Color	Clear liquid
Flash Point, Tag Closed Cup	None
Odor	Sight solvent odor
Percent Volatile	100%
Solubility in Water	Insoluble
Specific Gravity	1.45
Vapor Density (Air=1)	Approx. 4.5
Vapor Pressure	59 mm Hg @ 20°C
VOC Content	1450 grams/liter

Safety and Handling Precautions

Good ventilation is a must. Use self-contained, breathing apparatus if above TLV. Solvent resistant gloves and safety glasses, with splash protection, are required. All used and unused product should be disposed of in conformance with local, state and federal regulations. Keep out of reach of children. Treat this chemical with respect and follow all MSDS instructions.

Packaging

<u>Product Name</u>	<u>Part No.</u>	<u>Packaging</u>
Phase II	1290-55	55 Gal. Drum
Phase II	1290-5	5 Gal. Pail
Phase II	1290-4	4x1 Gal. Case