

Safe Strip G



Environmentally Preferred Paint & Coating Remover Gel Product Data Sheet

PO Box 9
Tucker, GA 30085
800-886-8240 • 770-621-8240
www.ecolink.com
email: info@ecolink.com

Description

SAFE STRIP G is a new, one-step, safe stripper in a viscous liquid that removes a multitude of coatings from a variety of surfaces. It contains no methylene chloride, methanol, toluene, acetone, methyl ethyl ketone, xylene or ethylene glycol ethers. It has a very slow evaporation without sacrificing performance. Its gel formulation adheres to overhead and vertical surfaces. It is thin enough to spray on and thick enough to stay on. Provides maximum safety and improved performance for all industrial maintenance applications.

Benefits

- Water soluble
- Biodegradable
- Non-carcinogenic
- Low VOC emissions in use
- Suitable for vertical surfaces
- No Methylene Chloride, MEK or Toluene
- One-step coatings removal

Applications

SAFE STRIP G effectively removes a variety of paints including high gloss alkyl enamel, varnish, acrylic latex and polyurethane. As a coatings remover, it can easily remove industrial adhesives, clearcoat, gaskets and seals.

SAFE STRIP G is an excellent replacement for gasket and adhesive solvents containing 1,1,1 trichloroethane, methylene chloride, acetone or toluene.

SAFE STRIP G's unique gel formulation may be brushed onto vertical and overhead surfaces. It is thin enough to be sprayed on but thick enough to stay put. SAFE STRIP G's slow evaporation eliminates multiple applications and high VOC emissions. Apply it once, let it work for 10-15 minutes, then scrape or rinse away softened coating.

Key Physical Characteristics

<u>Property</u>	<u>Typical Value</u>
Boiling Point	200° F
Evaporation Rate (nBuAc=1)	< 1
Flash Point, Tag Closed Cup	> 200° F
Odor	Sweet
Solubility in Water	Complete
Specific Gravity (H ₂ O=1)	1.03
pH of Solution	N/A
Physical Form	Thick, Clear Liquid
Vapor Pressure	< 1.00 mm Hg @ 68° F
Vapor Density (Air = 1)	> 3.0
VOC	969 gm/l

Safety and Handling Precautions

Avoid contact with eyes and skin. Wash thoroughly after handling. Avoid breathing mist or vapor. Use with adequate ventilation. Keep this container and vapors from this container away from heat and flame. Keep container closed.

If spilled, eliminate sources of ignition. Absorb with earth, sand or similar inert material and dispose of with solid waste according to federal, state and local regulations. Flush spill area with water. Consult MSDS.

Packaging

<u>Product Name</u>	<u>Part No.</u>	<u>Packaging</u>	<u>National Stock No.</u>
SAFE STRIP G	0389-55	55 Gal Drum	6850-01-454-6500
SAFE STRIP G	0389-5	5 Gal Pail	6850-01-454-6489
SAFE STRIP G	0389-1	4 x 1 Gal Case	
SAFE STRIP G	0389-66	12 Pt. Case	